
IGBT Power Module

- Half-bridge
- Including fast free-wheeling diodes
- Package with insulated metal base plate



Type	V_{CE}	I_C	Package	Ordering Code
BSM 100 GB 120 DN2K	1200V	145A	HALF-BRIDGE 1	C67070-A2107-A70

Maximum Ratings

Parameter	Symbol	Values	Unit
Collector-emitter voltage	V_{CE}	1200	V
Collector-gate voltage R_{GE} = 20 kΩ	V_{CGR}	 1200	
Gate-emitter voltage	V_{GE}	± 20	
DC collector current T_C = 25 °C T_C = 80 °C	I_C	 145 100	A
Pulsed collector current, t_p = 1 ms T_C = 25 °C T_C = 80 °C	I_{Cpuls}	 290 200	
Power dissipation per IGBT T_C = 25 °C	P_{tot}	 700	W
Chip temperature	T_j	+ 150	°C
Storage temperature	T_{stg}	-40 ... + 125	
Thermal resistance, chip case	R_{thJC}	≤ 0.18	K/W
Diode thermal resistance, chip case	R_{thJCD}	≤ 0.36	
Insulation test voltage, t = 1min.	V_{is}	2500	Vac
Creepage distance	-	20	mm
Clearance	-	11	
DIN humidity category, DIN 40 040	-	F	sec
IEC climatic category, DIN IEC 68-1	-	40 / 125 / 56	

Downloaded from Arrow.com.

Electrical Characteristics, at T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Static Characteristics					
Gate threshold voltage $V_{GE} = V_{CE}$, I_C = 4 mA	$V_{GE(th)}$	4.5	5.5	6.5	V
Collector-emitter saturation voltage V_{GE} = 15 V, I_C = 100 A, T_j = 25 °C V_{GE} = 15 V, I_C = 100 A, T_j = 125 °C	$V_{CE(sat)}$	 - -	 2.5 3.1	 3 3.7	
Zero gate voltage collector current V_{CE} = 1200 V, V_{GE} = 0 V, T_j = 25 °C V_{CE} = 1200 V, V_{GE} = 0 V, T_j = 125 °C	I_{CES}	 - -	 1.5 6	 2 -	mA
Gate-emitter leakage current V_{GE} = 20 V, V_{CE} = 0 V	I_{GES}	 -	 -	 400	nA
AC Characteristics					
Transconductance V_{CE} = 20 V, I_C = 100 A	g_{fs}	 54	 -	 -	S
Input capacitance V_{CE} = 25 V, V_{GE} = 0 V, f = 1 MHz	C_{iss}	 -	 6.5	 -	nF
Output capacitance V_{CE} = 25 V, V_{GE} = 0 V, f = 1 MHz	C_{oss}	 -	 1	 -	
Reverse transfer capacitance V_{CE} = 25 V, V_{GE} = 0 V, f = 1 MHz	C_{rss}	 -	 0.5	 -	


Downloaded from Arrow.com.

Electrical Characteristics, at T_j = 25 °C, unless otherwise specified


Parameter	Symbol	Values			Unit
		min.	typ.	max.	
Switching Characteristics, Inductive Load at T_j = 125 °C					
Turn-on delay time V_{CC} = 600 V, V_{GE} = 15 V, I_C = 100 A R_{Gon} = 6.8 Ω	$t_{d(on)}$	-	130	260	ns
Rise time V_{CC} = 600 V, V_{GE} = 15 V, I_C = 100 A R_{Gon} = 6.8 Ω	t_r	-	80	160	
Turn-off delay time V_{CC} = 600 V, V_{GE} = -15 V, I_C = 100 A R_{Goff} = 6.8 Ω	$t_{d(off)}$	-	400	600	
Fall time V_{CC} = 600 V, V_{GE} = -15 V, I_C = 100 A R_{Goff} = 6.8 Ω	t_f	-	70	100	
Free-Wheel Diode					
Diode forward voltage I_F = 100 A, V_{GE} = 0 V, T_j = 25 °C I_F = 100 A, V_{GE} = 0 V, T_j = 125 °C	V_F	- -	2.3 1.8	2.8 -	V
Reverse recovery time I_F = 100 A, V_R = -600 V, V_{GE} = 0 V di_F/dt = -1000 A/µs, T_j = 125 °C	t_{rr}	-	0.3	-	µs
Reverse recovery charge I_F = 100 A, V_R = -600 V, V_{GE} = 0 V di_F/dt = -1000 A/µs T_j = 25 °C T_j = 125 °C	Q_{rr}	- -	4 14	- -	µC

Downloaded from Arrow.com.


Power dissipation
$P_{tot} = f(T_C)$
parameter: $T_j \leq 150$ °C




Safe operating area
$I_C = f(V_{CE})$
parameter: $D = 0$, $T_C = 25$°C , $T_j \leq 150$ °C



Collector current
$I_C = f(T_C)$
parameter: $V_{GE} \geq 15$ V , $T_j \leq 150$ °C



Transient thermal impedance IGBT
$Z_{th\,JC} = f(t_p)$
parameter: $D = t_p / T$




Downloaded from Arrow.com.

Typ. output characteristics

$I_C = f(V_{CE})$


parameter: t_p = 80 µs, T_j = 25 °C



Typ. output characteristics

$I_C = f(V_{CE})$


parameter: t_p = 80 µs, T_j = 125 °C



Typ. transfer characteristics


$I_C = f(V_{GE})$

parameter: t_p = 80 µs, V_{CE} = 20 V




Downloaded from Arrow.com.


Typ. gate charge
$V_{GE} = f(Q_{Gate})$
parameter: $I_{C\ puls}$ = 100 A




Typ. capacitances
$C = f\ (V_{CE})$
parameter: V_{GE} = 0 V, f = 1 MHz



Reverse biased safe operating area
$I_{Cpuls} = f(V_{CE})$, T_j = 150°C
parameter: V_{GE} = 15 V



Short circuit safe operating area
$I_{Csc} = f(V_{CE})$, T_j = 150°C
parameter: V_{GE} = ± 15 V, t_{SC} ≤ 10 µs, L < 50 nH




Downloaded from Arrow.com.

Typ. switching time

$I = f(I_C)$, inductive load , T_j = 125°C


par.: V_{CE} = 600 V, V_{GE} = ± 15 V, R_G = 6.8 Ω



Typ. switching time

$t = f(R_G)$, inductive load , T_j = 125°C


par.: V_{CE} = 600 V, V_{GE} = ± 15 V, I_C = 100 A



Typ. switching losses

$E = f(I_C)$, inductive load , T_j = 125°C


par.: V_{CE} = 600 V, V_{GE} = ± 15 V, R_G = 6.8 Ω



Typ. switching losses

$E = f(R_G)$, inductive load , T_j = 125°C


par.: V_{CE} = 600V, V_{GE} = ± 15 V, I_C = 100 A



Downloaded from Arrow.com.

Forward characteristics of fast recovery reverse diode $I_F = f(V_F)$


parameter: T_j



Transient thermal impedance Diode


$Z_{th\,JC} = f(t_p)$

parameter: $D = t_p / T$



Downloaded from Arrow.com.


Circuit Diagram



Package Outlines

Dimensions in mm

Weight: 250 g



Downloaded from Arrow.com.

Nutzungsbedingungen

Die in diesem Produktdatenblatt enthaltenen Daten sind ausschließlich für technisch geschultes Fachpersonal bestimmt. Die Beurteilung der Geeignetheit dieses Produktes für die von Ihnen anvisierte Anwendung sowie die Beurteilung der Vollständigkeit der bereitgestellten Produktdaten für diese Anwendung obliegt Ihnen bzw. Ihren technischen Abteilungen.

In diesem Produktdatenblatt werden diejenigen Merkmale beschrieben, für die wir eine liefervertragliche Gewährleistung übernehmen. Eine solche Gewährleistung richtet sich ausschließlich nach Maßgabe der im jeweiligen Liefervertrag enthaltenen Bestimmungen. Garantien jeglicher Art werden für das Produkt und dessen Eigenschaften keinesfalls übernommen.

Sollten Sie von uns Produktinformationen benötigen, die über den Inhalt dieses Produktdatenblatts hinausgehen und insbesondere eine spezifische Verwendung und den Einsatz dieses Produktes betreffen, setzen Sie sich bitte mit dem für Sie zuständigen Vertriebsbüro in Verbindung (siehe www.eupec.com, Vertrieb&Kontakt). Für Interessenten halten wir Application Notes bereit.

Aufgrund der technischen Anforderungen könnte unser Produkt gesundheitsgefährdende Substanzen enthalten. Bei Rückfragen zu den in diesem Produkt jeweils enthaltenen Substanzen setzen Sie sich bitte ebenfalls mit dem für Sie zuständigen Vertriebsbüro in Verbindung.

Sollten Sie beabsichtigen, das Produkt in Anwendungen der Luftfahrt, in gesundheits- oder lebensgefährdenden oder lebenserhaltenden Anwendungsbereichen einzusetzen, bitten wir um Mitteilung. Wir weisen darauf hin, dass wir für diese Fälle
- die gemeinsame Durchführung eines Risiko- und Qualitätsassessments;
- den Abschluss von speziellen Qualitätssicherungsvereinbarungen;
- die gemeinsame Einführung von Maßnahmen zu einer laufenden Produktbeobachtung dringend empfehlen und gegebenenfalls die Belieferung von der Umsetzung solcher Maßnahmen abhängig machen.

Soweit erforderlich, bitten wir Sie, entsprechende Hinweise an Ihre Kunden zu geben.

Inhaltliche Änderungen dieses Produktdatenblatts bleiben vorbehalten.

Terms & Conditions of usage

The data contained in this product data sheet is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.eupec.com, sales&contact). For those that are specifically interested we may provide application notes.
Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify. Please note, that for any such applications we urgently recommend
- to perform joint Risk and Quality Assessments;
- the conclusion of Quality Agreements;
- to establish joint measures of an ongoing product survey, and that we may make delivery depended on the realization of any such measures.

If and to the extent necessary, please forward equivalent notices to your customers.

Changes of this product data sheet are reserved.

Downloaded from Arrow.com.