
PSR20-8-4-A

Ruland PSR20-8-4-A, 1/2" x 1/4" Four Beam Coupling, Aluminum, Set Screw Style, 1.250" OD, 1.500" Length





Description

Ruland PSR20-8-4-A is a set screw style four beam coupling with 0.5000" x 0.2500" bores, 1.250" OD, and 1.500" length. It is machined from a single piece of material and feature two sets of two spiral cuts. This gives it higher torque capacity, lower windup, and larger body sizes than single beam couplings. PSR20-8-4-A is zero-backlash and has a balanced design for reduced vibration at high speeds of up to 6,000 RPM. This four beam spiral coupling is zero-backlash and has a balanced design for reduced vibration at high speeds of up to 6,000 RPM. All hardware is metric and tests beyond DIN 912 12.9 standards for maximum torque capabilities. PSR20-8-4-A is made from 7075 aluminum for lightweight and low inertia. It is machined from bar stock that is sourced exclusively from North American mills and RoHS3 and REACH compliant. PSR20-8-4-A is manufactured in our Marlborough, MA factory under strict controls using proprietary processes.

Product Specifications

Bore (B1)	0.5000 in	**Small Bore (B2)**	0.2500 in
B1 Max Shaft Penetration	0.695 in	**B2 Max Shaft Penetration**	0.695 in
Outer Diameter (OD)	1.250 in	**Bore Tolerance**	+0.001 in / -0.000 in
Length (L)	1.500 in	**Recommended Shaft Tolerance**	+0.0000 in / -0.0005 in
Forged Set Screw	M6	**Screw Material**	Alloy Steel
Hex Wrench Size	3.0 mm	**Screw Finish**	Black Oxide
Seating Torque	7.2 Nm	**Number of Screws**	4 ea
Dynamic Torque Reversing	13 lb-in	**Angular Misalignment**	3.0°
Dynamic Torque Non-Reversing	26 lb-in	**Parallel Misalignment**	0.015 in
Static Torque	52 lb-in	**Axial Motion**	0.010 in
Torsional Stiffness	0.120 Deg/lb-in	**Moment of Inertia**	0.0340 lb-in^2
Maximum Speed	6,000 RPM	**Full Bearing Support Required?**	Yes
Zero-Backlash?	Yes	**Torque Wrench**	TW:BT-4C-3/8-64
Recommended Hex Key	Metric Hex Keys	**Material Specification**	7075-T651 Extruded and Drawn Aluminum Bar
Temperature	-40°F to 225°F (-40°C to 107°C)	**Finish Specification**	Bright, No Plating
Manufacturer	Ruland Manufacturing	**Country of Origin**	USA
Weight (lbs)	0.148400	**UPC**	634529034255
Tariff Code	8483.60.8000	**UNSPC**	31163003
Note 1	Torque ratings are at maximum misalignment.		
Note 2	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Note 3	Torque ratings for the couplings are based on the physical limitations/failure point of the machined beams. Under normal/typical conditions the hubs are capable of holding up to the rated torque of the machined beams. In some cases, especially when the smallest standard bores are used or where shafts are undersized, slippage on the shaft is possible below the rated torque of the machined beams. Please consult technical support for more assistance.		
Prop 65	⚠**WARNING** This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.		

Installation Instructions

1. Align the bores of the PSR20-8-4-A four beam coupling on the shafts that are to be joined and determine if the misalignment parameters are within the limits of the coupling. (*Angular*

Misialignment: 3°, *Parallel Misalignment*: 0.015 in, *Axial Motion*: 0.010 in)

2. Fully tighten the M6 screws on one hub to the recommended seating torque of 7.2 Nm using a 3.0 mm hex torque wrench.
3. Before tightening the screws on the second hub, rotate the coupling by hand to allow it to reach its free length.
4. Tighten the screws on the second hub to the recommended seating torque. Make sure the coupling remains axially relaxed and the misalignment angle remains centered along the length of the coupling.
5. The shafts may extend into the relieved portion of the bore as long as it does not exceed the shaft penetration length of 0.695 in.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Ruland Manufacturing:

MSP-6-SS ENCL20-6MM-A FHD-MCL-25-F MJS33-12-A MRSC25-5-5-A OF-MSP-20-F FHD-MCL-35-AN MCL-4-F MJS25-8-A MSPX-12-12-F ENSP20-10MM-A FSMR32-13-12-A MOCT19-5-A MRLC16-8-8-A MSP-22-F MSPX-8-8-F FHD-MCL-30-SS MJC57-25-A MSPC-16-16-F MSPX-16-16-F MTCL-12-1.75-F ENSP30-12MM-A MOCT57-25-A MQCL-8-A MSP-12-P MWC30-10-10-SS OCT12-4-A OD36/57-AT LV-MSP-25-SS MRSC13-5-5-A