

EVVOSEMI[®]

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC

Product Specification


▶ Domestic	Part Number	MMBTH10
▶ Overseas	Part Number	MMBTH10
▶ Equivalent	Part Number	MMBTH10

EV is the abbreviation of name EVVO

■ NPN Transistors

■ Features

- Collector Current Capability $I_C=0.05A$
- Collector Emitter Voltage $V_{CEO}=25V$



■ Simplified outline(SOT-23)

■ Classification of hfe

Marking	3EM
---------	-----







■ Absolute Maximum Ratings $T_a = 25^{\circ}C$

Parameter	Symbol	Rating	Unit
Collector - Base Voltage	V_{CBO}	30	V
Collector - Emitter Voltage	V_{CEO}	25	
Emitter - Base Voltage	V_{EBO}	3	
Collector Current - Continuous	I_C	0.05	A
Collector Power Dissipation	P_C	225	mW
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	556	$^{\circ}C/W$
Junction Temperature	T_J	150	$^{\circ}C$
Storage Temperature Range	T_{stg}	-55 to +150	



■ Electrical Characteristics $T_a = 25^{\circ}C$

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector- base breakdown voltage	V_{CBO}	$I_C = 100 \mu A, I_E = 0$	30			V
Collector- emitter breakdown voltage	V_{CEO}	$I_C = 1 mA, I_B = 0$	25			
Emitter - base breakdown voltage	V_{EBO}	$I_E = 10 \mu A, I_C = 0$	3			
Collector-base cut-off current	I_{CBO}	$V_{CB} = 25 V, I_E = 0$			100	nA
Emitter cut-off current	I_{EBO}	$V_{EB} = 2 V, I_C = 0$			100	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 4 mA, I_B = 0.4 mA$			0.5	V
Base - emitter saturation voltage	$V_{BE(sat)}$	$I_C = 4 mA, I_B = 0.4 mA$			1.2	
Base - emitter saturation voltage	V_{BE}	$V_{CE} = 10 V, I_C = 4 mA$			0.95	
DC current gain	h_{FE}	$V_{CE} = 10 V, I_C = 4 mA$	60			
Collector output capacitance	C_{ob}	$V_{CB} = 10 V, I_E = 0, f = 1 MHz$			0.7	pF
Transition frequency	f_T	$V_{CE} = 10 V, I_C = 4 mA, f = 100 MHz$	650			MHz


■ Typical Characteristics



■ Typical Characteristics



■ SOT-23



DIMENSIONS (mm are the original dimensions)

UNIT	A	A ₁ max.	b _p	c	D	E	e	e ₁	H _E	L _p	Q	v	w
mm	1.1 0.9	0.1	0.48 0.38	0.15 0.09	3.0 2.8	1.4 1.2	1.9	0.95	2.5 2.1	0.45 0.15	0.55 0.45	0.2	0.1

Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

EVVOSEMI:

[W01](#) [KBL608](#) [MMBT5401](#) [XL1509-5.0-EV](#) [TIP127](#) [DS18B20A20](#) [MJD122](#) [MMBD7000L](#) [GBU406](#) [SMCJ36A](#)
[KBPC1010](#) [SN74LVC1G02DBVR-EV](#) [SS210](#) [SS36F](#) [TL431](#) [1.5KE15A](#) [2SA1695](#) [GBJ3508](#)
[TPD1E05U06DPYR-EV](#) [USBLC6-4SC6-EV](#) [2SC5196](#) [AMS1117-ADJ](#) [P6SMB33A](#) [SMBJ5.0A](#) [SS8550](#)
[1N4148WT](#) [SN74LVC1G08DBVR-EV](#) [2SC3264](#) [MMBTA92](#) [TIP35C](#)