Push-in T-connector
CQT-12

Part number: 177687



General operating condition

Data sheet

Feature	Value
Nominal width	8.65 mm
Mounting position	Any
Pack size	1
Structural design	Push-pull principle
Operating pressure for entire temperature range	-0.95 bar ... 7 bar
Temperature-dependent operating pressure	-0.95 bar ... 15 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364 zone III
For use in the food industry	See supplementary material information
Ambient temperature	-25 °C ... 70 °C
Product weight	26 g
No. of outlets	2
No. of supply lines	1
Pneumatic connection 1	For piping system/pneumatic tubing outside diameter of 12 mm
Pneumatic connection 2	for piping system/pneumatic tubing outside diameter of 12 mm
Note on materials	RoHS-compliant
Housing material	POM
Releasing ring material	POM
Material of tube retaining claw	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

NPQH-T-Q14-E-P10 NPQP-LQ-R18-Q4-FD-P10 NPQP-Y-Q6-E-FD-P10 153367 NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-R12-Q12-FD QSY-6H-4 CRVZS-0.4 QSF-3/8-8-B 153031 DSBC-80-20-D3-PPSA-N3 HGL-1/8-QS-6 NPQP-L-Q10-E-FD-P10 QS-1/2-16 VABM-B10-25S-G38-6-P3 153269 QSS-8-F SASC-P4-A-M8-A NPQP-D-Q4-S8-FD-P10 QSF-1/4-8-B VABM-B10-25S-G38-10 VBQF-U-G14-E 153151 QS-10H-6 QSLL-G1/2-12 QSML-6 SGS-M10X1,25 153307 NPQP-T-Q8-E-FD-P10 QS-1/8-8-I