

TG-A09AB / TG-S09AB

Silicone Potting Compound

REACH Compliant | RoHS Compliant

Features

- Good thermal conductivity
- Protect electronic components after cured
- A:B=1:1
- Cured by room temperature or heating


Application:

Electronic Components - 5G, Aerospace, AI, AIoT, AR/VR/MR/XR, Automotive, Consumer Devices, Datacom, Electric Vehicle, Electronic Products, Energy Storage, Industrial, Lighting Equipment, Medical, Military, Netcom, Panel, Power Electronics, Robot, Servers, Smart Home, Telecom, etc.


Storage:

Silicone Potting Compound has a shelf-life of 12 months from the date of manufacture, as indicated by the lot number, when stored in the original, should be unopened container at or below 25°C.


Operation Manual



① Mix component A and B.



② Vacuum out air.



③ Pour potting compound.

Properties

Thermal Conductivity : 2.8 W/mK

0 0.8 1.2 1.4 1.6 1.7 1.8 2.2 3.2 3.6 4.0 4.5 5.0 15 20

Hardness : 90 (Shore OO)

0 10 20 30 40 50 60 70 100

Properties	Unit	TG-A09AB / TG-S09AB	Tolerance	Test Method
Thermal Conductivity	W/m•K	2.8	±10%	ASTM D5470 Modified
Color	-	Gray (Mix)	-	-
Dielectric Breakdown Voltage	KV/mm	≥11	-	ASTM D149
Volume Resistivity	Ohm-m	$\geq 10^{12}$	-	ASTMD257
Density	g/cm^3	2.52	±5%	ASTM D792
Operating temperature	° C	-50~+150	-	-
Tensile Strength @3.0mm	kgf/cm^2	230	-	ASTM D412
Elongation	%	55	-	ASTM D412
Viscosity	Pa·s	10~50	-	Brookfield
Weight Loss	%	<1	-	ASTM E595 Modified
Curing Time @25° C	Hrs	6	±10%	-
Curing Time @50° C	Hrs	0.6	±10%	-
Curing Time @80° C	Hrs	0.08	±10%	-
Standard Package	-	Pot	-	-
Hardness	Shore OO	90	±10	-
Mixing Ratio	gram	1:1	-	-

▶ Component A & Component B are mixed material. It is normal to cause precipitation and stratification due to different density. Well mixed component A before use by a flat spatula or other stainless tools to achieve the ideal thermal conductivity.

T-Global Technology (Europe & North America) Ltd.

Version19
20231228

Units 1-2 Cosford Business Park, Central Park, Lutterworth, Leicestershire, LE17 4QU, United Kingdom

T +44 (0)1455 553 510 **E** sales@tglobaltechnology.com **W** www.tglobaltechnology.com

NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film and release paper does not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment.
We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

t-Global Technology:

TGH-0130-02 T68A-270-270-0.055 TG-A482K-15-15-0.1-0 TG-AL373-310-310-3.0-0 TG-A1250-20-20-5.0
TG-T1000-28-28-0.25-5PT TG-AL373-19.5-12.7-0.5-0 TG-A1250-15-15-3.0 TG-A3500-10-10-0.5
TG-A1450-20-20-0.5 TG-A6200-20-20-1.5 TG-A1250LC-135-135-2.5 T62-1-15-15-0.16 TG-A2200-25-25-0.5
TG-A6200-10-5-0.5 TG-T1000-36-18-0.25-5PT T68APF-270-270-0.045 TG-A1780-5-5-0.5
TG-A1250-20-20-4.0 TG-A373F-150-150-0.25-2A TG-A6200-10-10-0.5 TG-APC94-150-150-0.5-0
TG-A3500-10-10-4.0 TG-A373F-300-300-0.25-1A TG-A4500-15-15-4.0 TG-A4500-40-40-0.5
TG-A1250-100-100-4.0 DC0001/05-TG-A482K-0.1-0 XL25W-TO220-18.5-12-1 TGH-0400-04