




MAPX	MODIFICATION	DATE

















RECOMMANDED PCB LAYOUT

PCB图仅供参考

Note:

1.Material:

1.1 Housing: High temperature thermoplastic with g.f,UL94v-0

1.2 Contact: copper alloy,t=0.20mm

1.3 Shell: copper alloy,t=0.25mm

2.Specification:

2.1 Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.

2.2 Dielectric withstanding voltage: 100 V(ac) for 1 min.

2.3 Contact resistance: 30 mΩ Max.

2.4 Insulation resistance: 100 MΩ Min.

2.5 Total mating force: 3.57 Kgf Max.

2.6 Total unmating force: 1.0 Kgf Min.

2.7 Temperature range: -30°C~80°C

产品图 PRODUCT CHART DWG		
公差一览表 TOLERANCE UNLESS OTHERMSE		
X.	±0.30	X. ±5.°
.X	±0.25	.X ±2.°
.XX	±0.20	.XX ±1.°
.XXX	±0.10	.XXX ±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	YANG	制图料号 PRODUCT PART NO.	920-B52A2021S10101
比例 SCALE	1:1	审核 CHKD	郭志富	产品名称 PRODUCT NO.	MICRO 5S B型6.4有边无柱有后盖两脚长1.0加焊脚短端SMT
日期 DATE	2019.11.23	核准 APPD	黄国荣	角法 VIEW	版本 VER A0

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Jing extension:

917-P81A202ES60201 918-418K2022Y40011 906-552A1012D10200 908-351A1011D10100
919-162A1012D10400 904-232B2032S10100 918-415K3028S40000 920-F52A2021S10105
904-232A2031S10100 905-761A2032S10200 910-151A2021D10100 911-221A2021S10100
906-752B1114D10200 916-151A1022Y10200 918-318K2023C40005 912-112A1011D10100
917-B88C201AH70201 920-154A2021Y10110 920-A62A2021S10104 920-A62A2021S10108
920-A64A2091S101A3 907-312A1101Y10210 912-312A1012D10100 906-262A1021D10200
907-111A1022D10200 912-112A2021S10100 918-468K2029Y50000 920-C52A2021S10105
920-C62A2021S10103 904-331B2032S10200