AQHV15-01ETG-C
ESD PROTECTION DIODE

Discription

The AQHV15-01ETG-C is designed to protect voltage sensitive components from damage or latch-up due to ESD. Excellent clamping capability, low leakage, and fast response time provide best in class protection on designs that are exposed ESD for board level. Because of its small size and bi-directional design, it is ideal for use in cellular phones, MP3 players,and portable applications that require audio line protection.



DFN1006-2L

Features

★ IEC 61000-4-2 Level 4 ESD Protection
- ± 30kV Contact Discharge
- ± 30kV Air Discharge

★ 250W Peak pulse Power (8/20us)
★ Low clamping voltage
★ Working voltage: 15V
★ Low leakage current
★ RoHS compliant
★ Protecting one bi-directional lines
★ Junction capacitance:25pF Typ.



Circuit Diagram

Applications

★ Cellular handsets and accessories
★ Battery Protection
★ Notebooks & Handhelds
★ Mobile Phones
★ MP3 Players
★ Peripherals

Ordering Information

Product ID	Pack	Qty(PCS)
AQHV15-01ETG-C	DFN1006-2L	10000


Absolute Ratings(Tamb = 25°C)

Symbol	Parameter	Value	Units
P_{PP}	Peak Pulse Power (t_p = 8/20 μ s)	288	W
T_L	Maximum lead temperature for soldering during 10s	260	°C
T_{stg}	Storage Temperature Range	-55 to +150	°C
T_{op}	Operating Temperature Range	-40 to +125	°C
T_j	Maximum junction temperature	150	°C
	IEC61000-4-2 (ESD) air discharge contact discharge	±30 ±30	KV
I_{PP}	Peak pulse current (tp=8/20us)@25°C	9	A


Electrical Characteristics

Symbol	Parameter	Test Condition	Min	Typ	Max	Units
V_{RWM}	Reverse Working Voltage				15.0	V
V_{BR}	Reverse Breakdown Voltage	I_T = 1mA	16.5			V
I_R	Reverse Leakage Current	V_{RWM} =15.0V			1.0	uA
V_C	Clamping Voltage	I_{PP} = 1A, t_p = 8/20μs		19.0	22.0	V
		I_{PP} = 9A, t_p = 8/20μs		28.0	28.0	V
C_J	Junction Capacitance	V_R = 0V, f = 1MHz		25		pF


Symbol	Parameters
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}



Typical Characteristics




Typical Application



Typical Interface Application

Outline And Dimensions



DFN1006-2L			
Dim	Min	Typ.	Max
A	0.46	0.48	0.50
A1	0	0.02	0.05
b	0.45	0.5	0.55
c	0.1	0.12	0.14
D	0.95	1.00	1.05
E	0.55	0.60	0.65
L	0.20	0.25	0.30
L1	0.035	0.05	0.065
h	0.07	0.12	0.17
All Dimensions in mm			

Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer’s products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer’s products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HXY MOSFET:

BZT52C3V3S HMCP602-I/SN HXY2300MI TPSMB100CA-VR SS510C BZT52C13 HAD8542ARZ HC3D10170A HT7150 MAX487ESA MMBT3904T HT7540-1 HXY2101EI P6SMB33CA SD15C SS10100 SS1045 HOPA2340UA HXY8205ES US2M PESD5V0S1BB TPSMB28A-VR SS5150B DTC143ZE HESDNC5VB1AF-B HC4D20120A IRLML6246PBF P6SMB36CA SQJA04EP-T1_BE3 P6SMB200A