Data Sheet

HUBER+SUHNER

Coaxial Cable Connector
16_MMCX-50-2-13/111_O

Description

Right angle cable plug

Interface standards
SUHNER-MMCX



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

Mechanical Data

Centre contact	soldered
Outer contact	soldered

Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00048327
Catalogue drawing	DCA-00091046
Assembly instruction	DOC-0000214734

Ordering Information

Bulk 100 pcs package	16_MMCX-50-2-13/111_OH
Single package	16_MMCX-50-2-13/111_OE

Additional Information

Suitable cables	SUCOFORM_86, EZ_86_TP_M17, MULTIFLEX_86

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Huber+Suhner:

6620_SMA-50-2/199_NE G032D/Nm/SMAm/1000 84093961 G032D/BNCm/BNCm/1000 RG_196_A/U PCRS_LCMX_LCMX_O421T_30.0_LL 12012090 1399.31.0020 85201112 G_03130_HT-01 24_SMA-50-2-15/111_NH 11_SMC-50-2-10/111_NE 11_TNC-50-3-116/133_NE 22511964 23002145 84118385 1399.17.0231 33_PC24-SK-50-2/199_NE Minibend L-10 16_MMCX-50-2-4/111_OH 6601_PC185-50-1/199_NE 6806.19.A MINIBEND R-8 RADOX 125 0.75 MMÂ² RED 11MMBXEF31616MMBX/300 12535682 1399.17.0210 23000457 MINIBEND R-10 MINIBEND R-12