
CUI DEVICES

SERIES: CP85-2 | **DESCRIPTION:** PELTIER MODULE

FEATURES

- solid state device
- 2-stage cooler
- precise temperature control
- quiet operation




RoHS

MODEL

MODEL	input voltage[1] max (Vdc)	input current[2] max (A)	output Qmax[3] T_h=27°C (W)	output Qmax[3] T_h=50°C (W)	output ΔTmax[4] T_h=27°C (°C)	output ΔTmax[4] T_h=50°C (°C)
CP854705-2	16.1	8.5	51.6	58	85	95

Notes:
1. Maximum voltage at ΔT max and T_h=27°C
2. Maximum current to achieve ΔT max
3. Maximum heat absorbed at cold side occurs at I_{max}, V_{max}, and ΔT=0°C
4. Maximum temperature difference occurs at I_{max}, V_{max}, and Q=0W (ΔT max measured in a vacuum at 1.3 Pa)

PART NUMBER KEY



SPECIFICATIONS


parameter	conditions/description	min	typ	max	units
internal resistance[1]		1.485	1.65	1.815	Ω
solder melting temperature	connection between thermoelectric pairs	138			°C
assembly compression				1	MPa
hot side plate				80	°C
RoHS	2011/65/EU				


Note: 1. Measured by AC 4-terminal method at 25°C

MECHANICAL DRAWING


units: mm

	MATERIAL	PLATING
ceramic plate	96% AL_2O_3	
wire leads	20 AWG	tin
sealer	silicon tubber 703 RTV (between cold and hot side plates)	
joint cover	scilicon rubber 703 RTV	
marking	P/N & S/N printed on cold side surface	






PERFORMANCE (Th=27°C)



PERFORMANCE (Th=50°C)



REVISION HISTORY

rev.	description	date
1.0	initial release	09/12/2016
1.01	brand update	10/30/2019

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

cuidevices.com

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Same Sky:

TBL004V-508-02BE-2GY CFM-2507CF-0140-313 CMC-5042PF-AC CPI-1375IC-80T TBP01R1-508-14BE
CDM1222-12A-FW-F16-050-67 CPM-2H PJ-058AH PJ-202AH TBP02P1-381-10BE
UJ32-C-H-G-L1-MSMT-TR CFM-2510B-0130-275 CFM-A238BF-270-651 SJ-2523-SMT-TR
CBT-09427-SMT-TR CFM-6015V-239-292-20 CMM-2718AT-42316-TR SJ-43516-SMT-TR-PI
CPT-1117-83-SMT-TR DS04-254-2-02BK-SMT PJ-047BH PR4-5V-450-1A TB007-508-02BE CMP-5247TF-K
DS01C-254-S-03BE HSE-B20350-NP PJ-067B SJ1-3535N CMA-4544PF-W CMI-9653S-SMT-TR