
One-way flow control valve CRGRLA-1/8-B

Part number: 161404





General operating condition

Data sheet

Feature	Value
Valve function	Flow control non-return function
Pneumatic connection 1	G1/8
Pneumatic connection 2	G1/8
Actuation type	Manual
Adjusting element	Slotted screw
Type of mounting	Screw-in
Standard nominal flow rate in flow control direction	340 l/min
Standard nominal flow rate in non-return direction	260 l/min ... 420 l/min
Operating pressure	0.03 MPa ... 1 MPa
Operating pressure	0.3 bar ... 10 bar
Operating pressure	4.35 psi ... 145 psi
Ambient temperature	-20 °C ... 80 °C
Maritime classification	See certificate
Explosion prevention and protection	Observe the information on the certificate Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Mounting position	Any
Symbol	00991452
Rotatability	360 deg/continuous swiveling not permissible
Standard flow rate in flow control direction 6 -› 0 bar	580 l/min
Standard flow rate in non-return direction at 6 -› 0 bar	530 l/min ... 590 l/min
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
LABS (PWIS) conformity	VDMA24364-B2-L
Suitability for the production of Li-ion batteries	Metals with more than 1% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils
Cleanroom class	Class 4 according to ISO 14644-1
Storage temperature	-10 °C ... 40 °C
For use in the food industry	See supplementary material information
Temperature of medium	-10 °C ... 60 °C
Nominal width	4 mm
Max. tightening torque	6 Nm

Feature	Value
Permissible actuation moment, adjusting screw	0.5 Nm
Product weight	37.8 g
Note on materials	RoHS-compliant
Seals material	FPM PVC
Hollow bolt material	High-alloy steel
Material of adjusting screw	High-alloy stainless steel
Swivel joint material	High-alloy stainless steel

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

153031 153307 QSML-6 153151 HGL-1/8-QS-6 NPQP-Y-Q6-E-FD-P10 QSLL-G1/2-12 QSY-6H-4 VABM-B10-25S-G38-6-P3 VBQF-U-G14-E QS-1/8-8-I QSF-1/4-8-B QSF-3/8-8-B SASC-P4-A-M8-A SGS-M10X1,25 DSBC-80-20-D3-PPSA-N3 153367 CRVZS-0.4 NPQH-T-Q14-E-P10 NPQP-D-Q4-S8-FD-P10 NPQP-T-Q8-E-FD-P10 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q4-FD-P10 NPQP-Y-R12-Q12-FD QS-1/2-16 QS-10H-6 QSS-8-F VABM-B10-25S-G38-10 153269 NPQP-LQ-R18-Q8-FD-P10