Key Features

AEC-Q200 Qualified

Thin film technology

Excellent overall stability

Sn termination on Ni barrier layer

Tight tolerance down to ±0.1%

Extremely low TCR down to ±10 PPM/°C

SMD enabled structure

Lead-free and RoHS compliant

Applications

Automotive (Non-safety parts)

Industrial

Telecommunication

Medical Equipment

Measurement/Testing Equipment

Type SMA-A series



The SMA-A series is a metal film precision MELF resistor with an SMD enabled structure tight tolerance and low TCR. A sister to our SMA series the SMA-A series is AEC-Q200 qualified

It comes in three sizes and six power ratings to 1W, is lead free and RoHS compliant.

Technical Specifications


Description	SMA-A0102		SMA-A0204		SMA-A0207	
Resistance range	1Ω-1MΩ; 0Ω		0.1Ω-3.4MΩ; 0Ω		0.1Ω-3.4MΩ; 0Ω	
Resistance tolerance	See below					
Temperature coefficient	See below					
Operation mode	Standard	High Power	Standard	High Power	Standard	High Power
Power rating P_{70}	0.2W	0.3W	0.25W	0.4W	0.5W	1W
Operating voltage U_{max}	200V	200V	200V	200V	300V	350V
Operating temperature range	-55℃~155℃					
Max. resistance change at P_{70} for resistance range, ΔR/R max., after 1000 h	≦0.5%		≦0.5%		≦0.5%	

Dimensions in millimetres unless otherwise specified

Dimensions Shown for reference purposes only. Specifications subject to change

For Email, phone or live chat, go to: www.te.com/help

Construction and Dimensions




①	Insulation Coating	④	Electrode Cap
②	Trimming Line	⑤	Resistor Layer
③	Ceramic Rod	⑥	Marking


Type	L (mm)	L_1 min. (mm)	ΦD (mm)	$ΦD_1$ (mm)	K (mm)	Weight 1,000EA (g)
SMA-A0102	2.20±0.10	1.1	1.10±0.10	D +0/-0.15	0.45±0.05	7.7
SMA-A0204	3.50±0.2	1.7	1.40±0.15	D +0/-0.2	0.8±0.1	18.7
SMA-A0207	5.90±0.2	2.9	2.20±0.20	D +0/-0.2	1.3±0.1	80.9

Recommended Land Pattern


Type	A (mm)	B (mm)	C (mm)
SMA-A0102	1.0	0.8	1.5
SMA-A0204	1.6	1.2	1.6
SMA-A0207	3.0	1.7	2.4



Soldering Condition




IR Reflow Soldering



Wave Soldering (Flow Soldering)

(1) Time of IR reflow soldering at maximum temperature point 260°C : 10s
(2) Time of wave soldering at maximum temperature point 260°C : 10s
(3) Time of soldering iron at maximum temperature point 410°C : 5s

Derating Curve



Dimensions in millimetres unless otherwise specified

Dimensions Shown for reference purposes only. Specifications subject to change

For Email, phone or live chat, go to: www.te.com/help

Standard Electrical Specifications

Size	Power Rating at 70°C	Max. Operating Voltage	Max. Overload Voltage	Resistance Range					TCR (PPM/°C)
				±0.1%	±0.25%	±0.5%	±1%	±5%	
0102	0.2W	200V	400V	100Ω-56KΩ				-	±15
					100Ω-82KΩ	49.9Ω-200KΩ	49.9Ω-390KΩ	-	±25
				-		1Ω-1MΩ			±50
				-			1Ω-1MΩ		±100
	Jumper: 2A			0Ω(<15mΩ)					-
0204	0.25W	200V	400V	49.9Ω-20KΩ					±10
				10Ω-300KΩ					±15
				10Ω-1MΩ		10Ω-3.4MΩ	4.02Ω-3.4MΩ		±25
				10Ω-1MΩ	1Ω-1MΩ	1Ω-3.4MΩ	0.2Ω-3.4MΩ		±50
				-			0.1Ω-1MΩ		±100
	Jumper: 2A			0Ω(<15mΩ)					-
0207	0.5W	300V	600V	49.9Ω-20KΩ					±10
				10Ω-300KΩ					±15
				10Ω-1MΩ		10Ω-3.4MΩ	4.02Ω-3.4MΩ		±25
				10Ω-1MΩ	1Ω-1MΩ	1Ω-3.4MΩ	0.2Ω-3.4MΩ		±50
				-			0.1Ω-1MΩ		±100
	Jumper: 4A			0Ω(<15mΩ)					-

High Power Rating Electrical Specifications

Size	Power Rating at 70°C	Max. Operating Voltage	Max. Overload Voltage	Resistance Range					TCR (PPM/°C)
				±0.1%	±0.25%	±0.5%	±1%	±5%	
0102	0.3W	200V	400V	100Ω-56KΩ				-	±15
				-	100Ω-82KΩ	49.9Ω-200KΩ	49.9Ω-390KΩ		±25
				-		1Ω-1MΩ			±50
				-			1Ω-1MΩ		±100
0204	0.4W	200V	400V	10Ω-300KΩ					±15
				10Ω-1MΩ		10Ω-3.4MΩ	1Ω-3.4MΩ		±25
				10Ω-1MΩ	1Ω - 1MΩ	1Ω – 3.4MΩ	0.2Ω-3.4MΩ		±50
				-			0.1Ω-1MΩ		±100
0207	1W	350V	700V	10Ω-300KΩ					±15
				10Ω-1MΩ		10Ω-3.4MΩ	1Ω-3.4MΩ		±25
				10Ω-1MΩ	1Ω - 1MΩ	1Ω – 3.4MΩ	0.2Ω-3.4MΩ		±50
				-			0.1Ω-1MΩ		±100

Operating Voltage=√(P*R) or Max. Operating Voltage listed above, whichever is lower
Overload Voltage=2.5*√(P*R) or Max. Overload Voltage listed above, whichever is lower.
RCWV(Rated Continuous Working Voltage)=√(P*R) or Max. Operating Voltage whichever is lower.
Operating temperature range - -55℃~155℃

Dimensions in millimetres unless otherwise specified


Dimensions Shown for reference purposes only. Specifications subject to change

For Email, phone or live chat, go to: www.te.com/help


Pulse withstanding capacity

The single impulse graph is the result of 50 impulses of rectangular shape applied at one-minute intervals. The limit of acceptance was a shift in resistance of less than 1% from the initial value. The power applied was subject to the restrictions of the maximum permissible impulse voltage graph shown

SMA-A Series Single Pulse(100 Ohm)




SMA-A0102 Series Single Pulse




Continuous Pulse

The continuous load graph was obtained by applying repetitive rectangular pulses where the pulse period was adjusted so that the average power dissipated in the resistor was equal to its rated power at 70°C. Again the limit of acceptance was a shift in resistance of less than 1% from the initial value


SMA-A series Continuous Pulse (100 Ohm)




SMA-A series Pulse Voltage (100 Ohm)



SMA-A0102 Continuous Pulse



SMA-A0102 Pulse Voltage (100 Ohm)




Frequency behaviour

Resistors are designed to function according to ohmic laws. This is basically true of resistors for frequencies up to 100kHz. At higher frequencies, there is an additional contribution to the impedance by an ideal resistor switched in series with a coil and both switched parallel to a capacitor. The values of the capacitance and inductance are mainly determined by the dimensions of the terminations and the conductive path length.

The environment surrounding components has a large influence on the behaviour of the component on the printed-circuit board.


Frequency Vs. Impedance

SMA-A0204




Frequency Vs Phase Angle

SMA-A0204




Frequency Vs Impedance

SMA-A0207



Frequency Vs Phase Angle


SMA-A0207




Lightning Surge

Resistors are tested in accordance with IEC 60115-1 using both 1.2/50us and 10/700us pulse shapes. The limit of acceptance is a shift in resistance of less than 0.5% from the initial value.


1.2/50µs Lightning Surge




10/700µs Lightning Surge



SMA-A0102 1.2/50µs Lightning Surge



SMA-A0102 10/700µs Lightning Surge



Environmental Characteristics


Item	Requirement	Test Method
Temperature Coefficient of Resistance (T.C.R.)	As Spec	**JIS-C-5201-1 4.8** **IEC-60115-1 4.8** -55°C~+125°C, 25°C is the reference temperature
Short Time Overload	10Ω-270KΩ: ±(0.1%+0.05Ω) <10Ω & >270KΩ: ±(0.15%+0.05Ω) 0102: ±(0.15%+0.05Ω)	**JIS-C-5201-1 4.13** **IEC-60115-1 4.13** RCWV*2.5 or Max. Overload Voltage whichever is lower for 5 seconds
Insulation Resistance	≥10G	**JIS-C-5201-1 4.6** **IEC-60115-1 4.6** Max. Overload Voltage for 1 minute
Endurance	10Ω-270KΩ: ±(0.25%+0.05Ω) <10Ω & >270KΩ: ±(0.5%+0.05Ω) 0102: ±(0.5%+0.05Ω)	**MIL-STD-202 Method 108** Condition D Steady State TA=125°C at derated power. Measurement at 24±4 hours after test conclusion.
Biased Humidity	10Ω-270KΩ: ±(0.5%+0.05Ω) <10Ω & >270KΩ: ±(1%+0.05Ω) 0102: ±(2%+0.05Ω)	**MIL-STD-202 Method 103** 1000 hrs 85°C/85%RH 10% of operating power.
High Temperature Exposure	10Ω-270KΩ: ±(0.25%+0.05Ω) <10Ω & >270KΩ: ±(1%+0.05Ω) 0102: ±(1%+0.05Ω)	**MIL-STD-202 Method 108** at +155°C for 1000 hrs
Board Flex	10Ω-270KΩ: ±(0.1%+0.05Ω) <10Ω & >270KΩ: ±(0.5%+0.05Ω) 0102: ±(0.5%+0.05Ω)	**AEC-Q200-005** Bending once for 60 seconds with 2mm
Solderability	95% min. coverage	**JIS-C-5201-1 4.17** **IEC-60115-1 4.17** **J-STD-002** 245±5°C for 3 seconds
Resistance to Soldering Heat	10Ω-270KΩ: ±(0.1%+0.05Ω) <10Ω & >270KΩ: ±(0.25%+0.05Ω) 0102: ±(0.25%+0.05Ω)	**MIL-STD-202 Method 210** 260±5°C for 10 seconds
Voltage Proof	No breakdown or flashover	**JIS-C-5201-1 4.7** **IEC-60115-1 4.7** 1.42 times Max. Operating Voltage for 1 minute
Leaching	Individual leaching area ≦5% Total leaching area ≦ 10%	**JIS-C-5201-1 4.18** **IEC-60068-2-58 8.2.1** 260±5°C for 30 seconds
Temperature Cycling	10Ω-270KΩ: ±(0.25%+0.05Ω) <10Ω & >270KΩ: ±(0.5%+0.05Ω) 0102: ±(1%+0.05Ω)	**JESD22 Method JA-104** -55°C to +125°C, 1000 cycles
Mechanical Shock	±(0.25%+0.05Ω)	**MIL-STD-202 Method 213** Wave Form: Tolerance for half sine shock pulse. Peak value is 100g's. Normal duration (D) is 6.

Environmental Characteristics (continued)

Item	Requirement	Test Method
Vibration	±(0.5%+0.05Ω)	**MIL-STD-202 Method 204** 5 g's for 20 min., 12 cycles each of 3 orientations, 10-2000 Hz
ESD	±(0.5%+0.05Ω)	**AEC-Q200-002** Human body, 2KV
Resistance to Solvents	No visible damage on appearance and marking	**MIL-STD-202 Method 215** Add Aqueous wash chemical - OKEM Clean or equivalent. Do not use banned solvents.
Terminal Strength	No broken	**AEC-Q200-006** Force of 1.8kg for 60 seconds.
Flammability	No ignition of the tissue paper or scorching of the pinewood board	**UL-94** V-0 or V-1 are acceptable. Electrical test not required.
RCWV(Rated Continuous Working Voltage)=√(P*R) or Max. Operating Voltage whichever is lower.		
Storage Temperature: 15~28°C; Humidity < 80%RH		


Packaging

Packaging Quantity and Reel Specification



Size	Reel Diameter	ΦA (mm)	ΦB (mm)	ΦC (mm)	W (mm)	T (mm)	Emboss Plastic Tape (EA)
0102	7"	178.5±1.5	60.0+1.0	13.0±0.2	9.0±0.5	12.5±0.5	3,000
0204	7"	178.5±1.5	60.0+1.0	13.0±0.2	9.0±0.5	12.5±0.5	3,000
0207	7"	178.5±1.5	60.0+1.0	13.0±0.2	13.0±0.5	15.5±0.5	2,000


Embossed Plastic Tape Specification



Size	A (mm) ±0.10	B (mm) ±0.10	W (mm) ±0.10	E (mm) ±0.10	F (mm) ±0.05	P0 (mm) ±0.10	P1 (mm) ±0.10	P2 (mm) ±0.05	ΦD0 (mm) ±0.10	T (mm) ±0.10
0102	1.30	2.40	8.0	1.75	3.50	4.00	4.00	2.00	1.50	1.50
0204	1.55	3.65	8.0	1.75	3.50	4.00	4.00	2.00	1.50	1.80
0207	2.40	6.15	12.0	1.75	5.50	4.00	4.00	2.00	1.50	2.70


Marking

E-24



Color	Digit	Multiplier
Silver	-	10^{-2}
Gold	-	10^{-1}
Black	0	10^{0}
Brown	1	10^{1}
Red	2	10^{2}
Orange	3	10^{3}
Yellow	4	10^{4}
Green	5	10^{5}
Blue	6	10^{6}
Violet	7	10^{7}
Grey	8	10^{8}
White	9	10^{9}

E-96



How To Order

SMA-A	0204	B	T	N	X	100R
Common Part	**Size**	**Tolerance**	**Packaging**	**TCR**	**Power Rating**	**Resistance Codes**
SMA-A MELF Resistor AEC-Q200 compliant	0102 0204 0207	B - 0.1% C - 0.25% D - 0.5% F - 1% J - 5%	T – Tape and Reel	B - ±10PPM/°C N - ±15PPM/°C C - ±25PPM/°C D - ±50PPM/°C E - ±100PPM/°C	T - 1W U - 0.5W X - 0.4W L - 0.3W V - 0.25W P - 0.2W	10R - 10Ω 100R - 100Ω 1K0 – 1,000Ω 10K – 10,000Ω 100K – 100,000Ω 1M0 – 1,000,000Ω

Dimensions in millimetres unless otherwise specified

Dimensions Shown for reference purposes only. Specifications subject to change

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

2-32562-2 1-1743284-2 1MM-HU-D10-VS-00-F-TBP 2-520128-2 2834055-1 CRGCQ0805F150R 1393431-1
1743455-2 281990-2 1-794222-0 2-292161-3 640174-1 650075-000 CRGCQ2010J3K3 SMW73R0JT
1969656-1 2-520103-2 2377783-2 35402K7FT 917790-2 141991-2 SMV3W5M6JT 1488167-1 292230-8
3-1393225-0 3430B2F51RTDF 917696-1 936348-1 352116RFT 36161