
Littelfuse
Expertise Applied | Answers Delivered

SL1003A Series



Agency Approvals

AGENCY	AGENCY FILE NUMBER
	E128662

3 Electrode GDT Graphical Symbol



Additional Information

Datasheet | Resources | Samples

Description

The SL1003A series has been especially developed for Broadband equipment. Special design features provide high levels of protection against fast rising transients in the 100V/µs to 1kV/µs range usually caused by lightning disturbances.

These devices have ultra low capacitance 1.5pF and present insignificant signal losses up to 1.5GHz. These devices are extremely robust and are able to divert a 5000A pulse without destruction. For AC Power Cross of long duration, over-current protection is recommended.

Features

- RoHS compliant
- Low insertion loss
- Surface mountable
- 5kA surge capability tested with 8/20/µs pulse as defined by IEC 61000-4-5
- GHz working frequency
- Excellent response to fast rising transients
- Can be used to meet Telcordia GR1089 without series resistance
- 10/700 6kV capability, as per ITU-Tk.21, enhanced test level
- 2000 Amp 2/10µs surge rating

Applications

- Broadband equipment
- ADSL equipment
- XDSL equipment
- Satellite and CATV equipment
- General telecom equipment

© 2017 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 12/12/17

Gas Discharge Tubes
SL1003A Series

Electrical Characteristics

Part Number	Device Specifications (at 25°C)								Life Ratings					
	DC Breakdown in Volts[1,2,3] (@100V/s)			Impulse Breakdown in Volts[2,3] (@100V/µs)	Impulse Breakdown In Volts[2,3] (@1kV/µs)	Insulation Resistance	Capacitance (@1MHz 0V Bias)	Arc Voltage (on state Voltage) @1Amp Min	Surge Life (@200A 10/1000µs)	Nominal Impulse Discharge Current (8/20µs)	Nominal AC Discharge Current (10x1s @50Hz)	AC Discharge Current (9 Cycles @ 50Hz)	DC Holdover Voltage[4]	Max Impulse Discharge Current (1 Application)
	MIN	TYP	MAX	MAX		MIN	MAX	TYP					TYP	@ 10/350µs
SL1003A090	72	90	108	600	700	$10^9\Omega$ (at 50V)	1.5 pF	~10 to 35 V	300 shots	10 shots (@10kA)	10 A	30 A	50 V	2 kA
SL1003A230	184	230	276			$10^9\Omega$ (at 100V)								
SL1003A250	200	250	300		750								135 V	
SL1003A260	210	260	310											
SL1003A300	240	300	360	750	850									
SL1003A350	280	350	420	800	900									
SL1003A400	320	400	480	850	950									
SL1003A450	360	450	540	900	1000									
SL1003A500	400	500	600	1100	1400									

Notes:
1. At delivery AQL 0.65 level II, DIN ISO 2859
2. In ionized mode, tested according to ITU-T Rec. K.12
3. Comparable to the silicon measurement Switching Voltage (Vs)
4. Reference REA PE-80, 0.2A. Tested to ITU-T Rec. K.12 and REA PE-80 < 150 msecs.

Product Characteristics

Materials	**Leaded Device:** Tin-plated copper wire **Core and Surface Mount:** Dull Tin-plated
Product Marking	Littelfuse 'LF' Mark, voltage and date code

Glow to Arc Transition Current	~1 Amp
Glow Voltage	~60 to 200 Volts
Storage and Operational Temperature	-40 to +90°C


© 2017 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 12/12/17

Device Dimensions


For SL1003A series:

Dimensions are in millimeters [and inches]


'R' Type Radial Lead Devices (SL1003AxxxR-001)




'C' Type Core Devices





'R' Type Radial Lead Devices (SL1003AxxxR and SL1003AxxxRF)





'SM' Type Surface Mount Devices







© 2017 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 12/12/17

Soldering Parameters - Reflow Soldering (Surface Mount Devices)

Reflow Condition		Pb-free assembly
Pre Heat	-Temperature Min ($T_{s(min)}$)	150°C
	-Temperature Max ($T_{s(max)}$)	200°C
	-Time (Min to Max) (t_s)	60 – 180 seconds
Average Ramp-up Rate (Liquidus Temp (T_L) to peak)		3°C/second max.
$T_{S(max)}$ to T_L - Ramp-up Rate		5°C/second max.
Reflow	-Temperature (T_L) (Liquidus)	217°C
	-Temperature (t_L)	60 – 150 seconds
Peak Temperature (T_P)		$260^{+0/-5}$ °C
Time within 5°C of Actual Peak Temperature (t_p)		10 – 30 seconds
Ramp-down Rate		6°C/second max.
Time 25°C to Peak Temperature (T_P)		8 minutes max.
Do not exceed		260°C



Soldering Parameters - Wave Soldering (Thru-Hole Devices)



Recommended Process Parameters:

Wave Parameter	Lead-Free Recommendation
Preheat: (Depends on Flux Activation Temperature)	(Typical Industry Recommendation)
Temperature Minimum:	100° C
Temperature Maximum:	150° C
Preheat Time:	60-180 seconds
Solder Pot Temperature:	280° C Maximum
Solder Dwell Time:	2-5 seconds

Soldering Parameters - Hand Soldering

Solder Iron Temperature: 350° C +/- 5°C
Heating Time: 5 seconds max.

© 2017 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 12/12/17


Packaging

'C' Type Core Items: Package bulk pack in polybag, 500 pcs/bag


'R' and 'RF' Type Radial Lead Items: Packed in tray, 100 pcs/tray

'SM' Type Surface Mount Items: Packaged tape and reel carrier, 700 pcs/reel (specifications below)

Dimensions are in millimeters [and inches]



Dimensions are in millimeters [and inches]



SMD-tape according to IEC 60286-3

Part Numbering System and Ordering Information

SL1003 A XXX XX

Type 3 Pole Arrestor
Voltage
Pin Configuration

C = Core type (Packed in polybag, 500pcs/bag)
R = Radial Lead without Failsafe (Packed in tray, 100pcs/tray)
RF = Radial Lead with Failsafe (Packed in tray, 100pcs/tray)
SM = Surface Mount (Packed in carrier and tape, 700pcs/reel)

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littelfuse.com/disclaimer-electronics.

© 2017 Littelfuse, Inc.
Specifications are subject to change without notice.
Revised: 12/12/17

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Littelfuse:

0233006.MXP 03420828H 37014000430 SL1011A230A 0242.080UAT1 1812L260/12MR MDSR-4-22-38 RF1342-000 RF2562-000 RF2682-000 RF3304-000 1812L150/24MR 2920L600/12MR IXTP52P10P PAA140S RF3305-000 SM12-02HTG TPSMD33CA 03540601ZXGY 60R250XF RF1543-000 1.5SMC51CA 8.0SMDJ16CA DNA30E2200PA V150LA20AP P3100SBLRP 0327020.LXS 0481010.HXLP NANOSMDC200F-2 TP5.0SMDJ43CA