


REV. 0
DCO 142026

COIL: @ 25°C

RESISTANCE	1350 OHMS ± 10%
NOMINAL VOLTAGE	26.5 VDC
MUST OPERATE	13.5 VDC
MUST RELEASE	8.1 VDC MAX, 1.5 VDC MIN.

ENVIRONMENT:


VIBRATION 10 CPS TO 3000 CPS @ 30 g's

SHOCK 75 g's 6 MS. DURATION

TEMPERATURE -65 °C TO +125 °C

NOTES: OPERATE & RELEASE 4 MS MAX.
CONTACT STABILIZATION TIME 2.5 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO
2 AMPS 28 VDC RESISTIVE
50,000 OPERATIONS

DR. PBB 5/22/00 | CK. TLG 9-13-00

COMMUNICATIONS INSTRUMENTS, INC.

CUST. QPL
CUST. NO. M39016/13-057M REV.

"3SBC" RELAY

3SBC1518A2

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TE Connectivity:

3430B2F51RTDF 141991-2 1969656-1 2-292161-3 650075-000 917696-1 U5254-000005-030PA 1903112-2 2834055-1 2377783-2 1743455-2 936348-1 3631B101LL CRGCQ2010J3K3 ROX05SJ18R SBCHE154R7K 1393431-1 175977-2 TE50BR39J 1-794222-0 MPT100C18RF SBCHE64R7K 2005330-1 2310537-1 3-1393225-0 CPF0402B37K4E1 RH73H2A40MKTN SMW73R0JT 1-962915-1 2380312-2