

Self-aligning ball bearings, cylindrical and tapered bore, cylindrical bore, unsealed

Principal dimensions			Basic load ratings		Fatigue load limit	Speed ratings		Mass	Designation
			dynamic	static		Reference speed	Limiting speed		
d	D	B	C	C_0	P_u				
mm			kN		kN	r/min		kg	-
20	47	14	12,7	3,4	0,18	32000	20000	0,12	1204 ETN9





Calculation factors

e 0,3
Y_1 2,1
Y_2 3,3
Y_0 2,2

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

SKF:

16052 MA UCF 310 SNL 518-615 2211 EKTN9/C3 6205-2Z/VA208 99114 NJ 309 ECJ/C3 W61903-2RS1 NU 2313 ECML/C3 22234 CCK/C3W33 22344 CC/C3W33 3210 ATN9 FYJ 50 TF FYJ 65 KF 24044 CCK30/W33 FYJ 30 TF NU 1022 ML TSN 528 S 23056 CC/W33 6012-2Z/C3 6213-2Z N 318 ECM SY 45 TF 61840 MA 6219-2Z/C3 6226-2Z/C3 23972 CC/W33 6211/C3 NUP 208 ECP TKRS 11