# Anti-static series electronics pliers

## Compact models for manoeuvrability

▷ ISO 9654, DIN ISO 9654, NF ISO 9654.
• Slimmer bullet-nose profile combines cutting performance with manoeuvrability.
• Model 405 is suitable for cutting piano wire Ø 0.4 mm.
⚖ : 65 g.

| | Cut | Cu - Ni wire Ø mm | Fe wire 30 HRc Ø mm |
|---|---|---|---|
| **405.E** | | 0,3 - 1,3 | 0,7 |
| **406.E** | | 0,1 - 1,3 | 0,7 |
| **407.E** | | 0,1 - 1,3 | |






## Stocky models for versatility

▷ ISO 9654, DIN ISO 9654, NF ISO 9654.
• Clean cut in a variety of materials, from copper to piano wire -> 0.5 mm.
• Available with offcut retaining system.
⚖ : 65 g.

| | Cut | Cu - Ni wire Ø mm | Fe wire 30 HRc Ø mm | Offcut retainer |
|---|---|---|---|---|
| **405.10E** | | 0,3 - 1,4 | 0,8 | |
| **405.10RE** | | 0,3 - 1,2 | 0,7 | • |






## Long-reach models for accessibility

▷ ISO 9654, DIN ISO 9655, NF ISO 9654.
• Up to 1.5 to 2 mm more reach than standard cutting pliers
• Available with offcut retaining system.
⚖ : 65 g.

| | Cut | Cu - Ni wire Ø mm | Fe wire 30 HRc Ø mm | Offcut retainer |
|---|---|---|---|---|
| **425.E** | | 0,1 - 1,3 | | |
| **435.E** | | 0,1 - 1,3 | 0,7 | |
| **435.RE** | | 0,1 - 1,2 | 0,7 | • |






## Slim-nose models with back clearance

▷ ISO 9654, DIN ISO 9655, NF ISO 9654.
• For cutting behind components and reaching under obstacles such as coils or resistors.
• Anti-static user-comfort type only.
⚖ : 65 g.

| | Cut | Cu - Ni wire Ø mm | Fe wire 30 HRc Ø mm |
|---|---|---|---|
| **436.E** | | 0,1 - 1,2 | 0,7 |
| **426.E** | | 0,1 - 1,2 | |






## Heavy-duty models

▷ ISO 9654, DIN ISO 9654, NF ISO 9654.
• For tough applications and repetitive work on a wide range of materials.
• Piano wire : 405.12 C : 0.8 mm; 405.12 RC : 0.6 mm.
• Available with offcut retaining system.
⚖ : 105 g.

| | Cut | Cu - Ni wire Ø mm | Cu - Ni wire Ø mm | Offcut retainer |
|---|---|---|---|---|
| **405.12E** | | 0,4 - 2,0 | 1,0 | |
| **405.12RE** | | 0,4 - 1,5 | 0,9 | • |
| **415.E** | | 0,3 - 2,0 | 1,0 | |
| **415.RE** | | 0,3 - 1,5 | 0,8 | • |






# Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

## FACOM:

R.5.5 AEF.J6 AT2.5X50VE ATD0X75VE ATWH6.5X150CK CR.LPTPB RL.NANO-U1 427.E 440.14 S.210 467BF.9 R.5.5LA RB.40AE 440.19 AEX.7X35 AT6.5X300 NSVL.J5APB R.360NANO 39.13 ATP0X75VE ES.002 714A-L DELA.1257.06 251A.1,5 257.GPB 76.JE16 ATPA4V.J12IPB 440.6 485.17 ATDVE.J6PB