Documentation & Additional Information

Product Drawings:
- None Available

Catalog Pages/Data Sheets:
- None Available

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files:
- None Available

List all Documents

Additional Information:
- Product Line Information

Related Products:
- Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:
- Product Type = Heat Shrinkable Tubing
- Material = Polytetrafluorethylene (PTFE)
- Color = Clear

Electrical Characteristics:
- Product Source = U.K.
- Expanded ID, Min. (mm [in]) = 2.30 [0.091]
- Recovered ID, Max. (mm [in]) = 1.55 [0.061]
- Product Use = Couplings, Hydraulic Hose
- Cut Length (mm [in]) = 1220.00 [48.068]

Body Features:
- Product Name = TFE
- Pliancy = Flexible
- Wall Style = Thin
- Wall Type = Single
- Shrink Ratio = 1.8:1
- Fluid Type = Brake Fluid, Chemicals/Solvents, Water
- Resistant To = Fluids, Mechanical Damage
- Wall Thickness - Full Recovery (Nominal) (mm [in]) = 0.30 [0.012]

Housing Features:
- Material Systems = No
- Flammability Rating Type = Flame-Retardant

Industry Standards:
- UL Rating = None
- CSA Certified = No
- Approved Standards = BS 4G-198 Part 4 Type
  Type 5B, SAE AMS-DTL-23053/12
- RoHS/ELV Compliance = RoHS compliant, ELV
- Lead Free Solder Processes = Not relevant for
- RoHS/ELV Compliance History = Always was R

Environmental:
- Fluid Resistance = Splash Protection
- Operating Temperature (°C) = -67 – +250

Conditions for Usage:
- Full Recovery Temperature (°C) = 340
- Shrink Temperature, Min. (°C) = 340
- High Temperature Compatible = Yes

Operation/Application:
- Application = Insulation and Protection
- Emission Free = No

Packaging Features:
- Packaging Method = Stick

Other:
- Brand = Raychem

© 2012 Tyco Electronics Corporation, a TE Connectivity Ltd. company. All Rights Reserved | Privacy Policy

Downloaded from Arrow.com.