
Inductive sensor

NJ2-12GM-N-V1



- 2 mm flush
- Usable up to SIL 2 acc. to IEC 61508

Dimensions



Technical Data

General specifications		
Switching function		Normally closed (NC)
Output type		NAMUR
Rated operating distance	s_n	2 mm
Installation		flush
Assured operating distance	s_a	0 ... 1.62 mm
Reduction factor r_{Al}		0.4
Reduction factor r_{Cu}		0.3
Reduction factor r_{304}		0.85
Output type		2-wire
Nominal ratings		
Nominal voltage	U_o	8.2 V (R_i approx. 1 kΩ)
Operating voltage	U_B	5 ... 25 V
Switching frequency	f	0 ... 2000 Hz

Release date: 2020-12-14 Date of issue: 2020-12-14 Filename: 106397_eng.pdf

Technical Data


Hysteresis	H	3 %
Suitable for 2:1 technology		yes , Reverse polarity protection diode not required
Current consumption		
Measuring plate not detected		≥ 3 mA at nominal voltage
Measuring plate detected		≤ 1 mA at nominal voltage
Functional safety related parameters		
Safety Integrity Level (SIL)		SIL 2
$MTTF_d$		5887 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Compliance with standards and directives		
Standard conformity		
NAMUR		EN 60947-5-6:2000 IEC 60947-5-6:1999
Standards		EN 60947-5-2:2007 EN 60947-5-2/A1:2012 IEC 60947-5-2:2007 IEC 60947-5-2 AMD 1:2012
Approvals and certificates		
IECEx approval		
Equipment protection level Ga		IECEx PTB 11.0037X
Equipment protection level Gb		IECEx PTB 11.0037X
Equipment protection level Da		IECEx PTB 11.0037X
Equipment protection level Mb		IECEx PTB 11.0037X
ATEX approval		
Equipment protection level Ga		PTB 00 ATEX 2048 X
Equipment protection level Gb		PTB 00 ATEX 2048 X
Equipment protection level Da		PTB 00 ATEX 2048 X
EAC conformity		TR CU 012/2011
FM approval		
Control drawing		116-0165
UL approval		cULus Listed, General Purpose
Ordinary Location		E87056
Hazardous Location		E501628
Control drawing		116-0452
CSA approval		cCSAus Listed, General Purpose
CCC approval		
Hazardous Location		2020322315002255
NEPSI approval		
NEPSI certificate		GYJ16.1393X
ANZEx		18.3018X
Marine approval		DNVGL TAA00001A5
Ambient conditions		
Ambient temperature		-25 ... 100 °C (-13 ... 212 °F)
Mechanical specifications		
Connection type		Connector plug
Housing material		Stainless steel 1.4305 / AISI 303
Sensing face		PBT
Degree of protection		IP67
Connector		
Threading		M12 x 1
Number of pins		4
General information		
Scope of delivery		2 self locking nuts in scope of delivery

Release date: 2020-12-14 Date of issue: 2020-12-14 Filename: 106397_eng.pdf


Technical Data

Use in the hazardous area		see instruction manuals

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-6

1	BN	(brown)
2	BU	(blue)

Accessories

	**V1-G-N-2M-PUR**	Female cordset single-ended M12 straight A-coded, 2-pin, PUR cable blue, NAMUR
	**V1-W-N-2M-PUR**	Female cordset single-ended M12 angled A-coded, 2-pin, PUR cable blue, NAMUR
	**EXG-12**	Quick mounting bracket with dead stop
	**BF 12**	Mounting flange, 12 mm

Release date: 2020-12-14 Date of issue: 2020-12-14 Filename: 106397_eng.pdf

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

PEPPERL+FUCHS:

OBR5000-18GK40A-E2 CCN15-30GS60-E2-V1 NBB0.8-5GM25-E2 WCS3-MH1 BF18 MH4-2057 NBB2-12GM50-A2-V1 S1SD-1AI-1U.1 UBE800-F77-SE2-V31 NBB5-18GM50-A0 UB2000-F42-E6-V15 114642 NBB0.8-4M25-E0 NBB8-18GM50-E0 OQT150-R101-2EP-IO-V31 134143 KLR-C02-2,2-2,0-K70 NBB1-4GM22-E2 NBB2-12GM50-E2 OBR12M-R100-2EP-IO-V31-L OBR2500-12GM40-E5 OBD450-18GK40A-E2 UB800-18GM40-I-V1 34441 GLV30-8-2500/47/73C NBB4-12GM50-A2-V1 NBB5-18GM50-E2 24772 NBB2-8GM40-E0-V1 OQT150-R100-2EP-IO-V31-L