Specification Sheet

Part Number: 318-60158



Heat Shrink Tubing, 4' Long Stick, Adhesive Lined, 3:1 Shrink Ratio, 1.5", 40.0/13.0 Dia, PO, Black, 6/pkg

Article Number	318-60158
Type	TAN33-ST-40/13 BK
Color	Black (BK)
Features & Benefits	• Adhesive lining provides an excellent seal against moisture and humidity. • Thin exterior wall is very flexible, while providing superior insulation of cables and components. • 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters. • Meets UL224 VW-1 specifications, making it ideal for high heat applications (excludes clear tubing). • Polyolefin material provides mechanical strength with good resistance to solvents, oils and fuels. • 4-foot sticks are individually tagged and come in a retail box.
Quantity Per	pack

Product Description	TAN33 is a flexible, thin wall adhesive-lined heat shrink tubing with highly flame retardant properties. The 3 to 1 shrink ratio accommodates a wide range of component shapes and diameters. The adhesive lining begins to activate as the temperature reaches 176° F (80° C), to create a strong seal against moisture and humidity.
Short Description	Heat Shrink Tubing, 4' Long Stick, Adhesive Lined, 3:1 Shrink Ratio, 1.5", 40.0/13.0 Dia, PO, Black, 6/pkg
Global Part Name	TAN33-ST-40/13 BK-PO-X-BK
Length L (Imperial)	4.0
Length L (Metric)	1.22
Variant	Thin-Wall
Nominal Diameter (Imperial)	1-1/2
Nominal Diameter (Metric)	40
Wall Thickness WT (Imperial)	.094
Wall Thickness WT (Metric)	2.40
Material	Polyolefin, cross-linked (PO-X)
Material Shortcut	PO-X
Adhesive	Hot melt adhesive

Halogen free	No
Operating Temperature (Metric)	-67°F to +257°F (-55°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes

Package Quantity(Imperial)	6
Package Quantity (Metric)	6
Customs Number	3926909987

© 2018 HellermannTyton. All rights reserved.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HellermannTyton:

111-01950 T18R-PA66HS-BK 111-08229 T80I-PA66-NA 156-00007 T50ROSEC24-PA66HS/PA66HIRHS-BK A801632T 156-02742 SRC150M8-PA6GF30-BK 300-30163 HIS-PACK-1.6/0.8-PO-X-CL 151-00503 RB14-PA66-NA 151-02993 EC1-3TL7OTP-PA66HIRHS-BK 166-31002 PCS16-FM-M16-NPB-ML 308-30151 HIS-3-BAG-1.5/0.5-PO-X-BK 518-05025 HGPC2-5-PVC-Special 156-00876 401-52880 152-42-G-PO-X-BK 450-20004 RMS 43-10-PO-X-BK EL322 151-00128 SACTC12-MET-WH 161-64405 HWPP25L2-PP-GY 633-02070 HV1207-PVC-FR-BK 115-40300 REZ300-PA66-BK 111-81919 IT18FL-PA66-NA 115-02300 RELK2L-PA66-BK 151-10930 CTQM5-PA66-BK 308-30612 HIS-3-BAG-6/2-PO-X-BU 308-31206 HIS-3-12/4-PO-X-BU 151-01944 151-03547 CMRCCHM6-PA66HIRHSUV-BK 151-03556 CMRCCSMM8-PA66HIRHSUV-BK 151-14003 RB5-PA66-NA 151-27019 LKC-PA66-NA 317-00072 TX46-11.6/2.5-PO-X-BK