
FFD-28SS-R102
Rotary/Friction Damper

Bansbach easylift®



SPECIFICATIONS

Model	Max Torque	Max Reverse Torque	Max Rotation Speed
FFD-28SS-R102	0.1±0.01 Nm (1±0.1 kgfcm)	Clockwise	30 RPM


Max Cycle Rate	Operating Temperature	Weight	Body & Cap Material	Cap Color
13 cycles/min.	-10 ~ 60˚C (90%RH)	14±2g	POM	Black

* Rated torque is measured at a rotation speed of 20rpm at 20-25°C

HOW TO USE THE DAMPER

1. The damper generates torque in both the clockwise and counter-clockwise directions. (A one-way clutch is built in inside the damper.)

2. Please make sure that the shaft attached to a damper has a bearing, as the damper itself is not fitted with one.

Shaft's external dimensions	Ø8 $^{0}_{-0.03}$
Surface hardness	HRC55 or higher
Quenching depth	0.5mm or higher
Surface roughness	1.0Z or lower
Chamfer end (Damper insertion side)	

3. It can be used as a free-stop for a load that is smaller than the rated torque.

4. Please refer to the recommended dimensions in the chart when creating a shaft for attachment to the damper. Using a shaft outside of the recommended dimensions may cause the shaft to slip out.

5. To insert a shaft into the damper, insert the shaft while spinning it in the opposite direction of the damper's direction of torque generation. (Do not force the shaft in from a regular direction. This may damage the built-in oneway clutch.)

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

BANSBACH EASYLIFT:

K0N0BK2-100-280-355N W4W4-96-075-255--001/000N D0M0ZF3-305-400-270N K0N0KK2-150-460-890N
B0N0N40-200-462-065N D0M0ZF3-305-400-355N H0N0F42-100-264-535N V0V0N56-100-230-135N
B0N0F40-210-473-445N D0M0ZF3-100-195-355N H0N0N42-410-862-445N A0A0N40-140-349-270N
A0A0N40-210-473-580N B0N0F40-200-455-225N D3D3XB1-100-310/000N FFD-25SS-R103
K0N0BK2-510-1095-180N K0N0KK2-200-589-1110N B0N0N40-210-473-270N D0M0F55-150-362-890N
FK-1210H-S H0N0F42-400-847-110N V0V0F46-090-207-090N D0M0N45-203-480-1555N
H0N0F42-300-647-1110N K0N0BK2-305-685-1110N D0M0ZF3-100-195-180N D0M0ZF3-305-400-180N
H0N0F42-150-347-270N V0V0N56-100-230-225N