# 867/1 Z IP TORX PLUS® bits, 7 IP x 25 mm

## Bits for TORX PLUS® Screws




| | | | |
|---|---|---|---|
| **EAN:** | 4013288031563 | **Size:** | 25x7x7 mm |
| **Part number:** | 05066276001 | **Weight:** | 5 g |
| **Article number:** | 867/1 IP TORX PLUS® | **Country of origin:** | CZ |
| | | **Customs tariff number:** | 82079030 |

- For TORX PLUS® screws
- Ductile and tough for hard materials
- 1/4" hexagon drive (Wera connecting series 1)
- Suitable for Bosch, Fein, Holz-Her, Lecreux, Metabo
- Prevents premature breakage of the drive tip

High quality bits for recessed TORX PLUS® screws. Tough viscous for universal use. ¼" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

**Web link**
http://products.wera.de/en/tools_for_the_aerospace_segment_the_range_of_bits_bits_for_torx_plus_screws_867_1_ip_torx_plus.html



Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

## TORX PLUS®




Compared with the “normal” TORX® profile, the elliptical instead of circular profile enlarges the 6 flanks that transfer torque between the tool and the screw. This means that the force applied when screwdriving is spread across a larger surface area. Higher torque is transferred and, in addition, the service life of the screw and tool are lengthened. The so-called centre-lock screws on cutting tools represent a typical use of this type of screw profile. The thermal influences on such holders for carbide insert tips often “bake” the retaining screws so firmly that it is important to have a profile that considerably enhances the loosening torque capability of the screws. For this reason a torque-stable screw profile is necessary to avoid any possible damage to the screw and to exclude the possibility of an otherwise costly machine downtime.

## Tough-absorbing bits




Tough-absorbing Wera bits (Z) prevent any premature breakage of the drive tip.

**Web link**
http://products.wera.de/en/tools_for_the_aerospace_segment_the_range_of_bits_bits_for_torx_plus_screws_867_1_ip_torx_plus.html

Wera - 867/1 IP TORX PLUS®
05066276001 - 4013288031563

Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Further versions in this product family:

| | | mm | inch |
|---|---|---|---|
| 05135120001 | IP 1 | 25 | 1 |
| 05135121001 | 2 IP | 25 | 1 |
| 05160956001 | 3 IP | 25 | 1 |
| 05134695001 | 4 IP | 25 | 1 |
| 05066272001 | 5 IP | 25 | 1 |
| 05066274001 | 6 IP | 25 | 1 |
| **05066276001** | **7 IP** | **25** | **1** |
| 05066278001 | 8 IP | 25 | 1 |
| 05066279001 | 9 IP | 25 | 1 |
| 05066280001 | 10 IP | 25 | 1 |
| 05066282001 | 15 IP | 25 | 1 |
| 05066284001 | 20 IP | 25 | 1 |
| 05066286001 | 25 IP | 25 | 1 |
| 05066287001 | 27 IP | 25 | 1 |
| 05066288001 | 30 IP | 25 | 1 |
| 05066290001 | 40 IP | 25 | 1 |

Web link
http://products.wera.de/en/tools_for_the_aerospace_segment_the_range_of_bits_bits_for_torx_plus_screws_867_1_ip_torx_plus.html



Wera Werkzeuge GmbH
Korzerter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de