
PNP Low-Saturation Transistor

NZT660, NZT660A



1. Base
2. & 4. Collector
3. Emitter

SOT−223
CASE 318H

Description

These devices are designed with high−current gain and low saturation voltage with collector currents up to 3 A continuous.

ABSOLUTE MAXIMUM RATINGS

(T_A = 25°C unless otherwise noted.) (Notes 1, 2)

Symbol	Parameter	Value	Unit
V_{CEO}	Collector−Emitter Voltage	−60	V
V_{CBO}	Collector−Base Voltage NZT660 NZT660A	 −80 −60	V
V_{EBO}	Emitter−Base Voltage	−5	V
I_C	Collector Current − Continuous	−3	A
T_J, T_{STG}	Operating and Storage Junction Temperature Range	−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. These ratings are based on a maximum junction temperature of 150°C.
2. These are steady limits. **onsemi** should be consulted on application involving pulsed or low−duty−cycle operations.


THERMAL CHARACTERISTICS

(T_A = 25°C unless otherwise noted.) (Note 3)

Symbol	Parameter	Max	Unit
P_D	Total Device Dissipation	2	W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	62.5	°C/W

3. PCB size: FR−4, 76 mm × 114 mm × 1.57 mm (3.0 inch × 4.5 inch × 0.062 inch) with minimum land pattern size.

MARKING DIAGRAM



A = Assembly Location
Y = Year
W = Work Week
660(A) = Specific Device Code

ORDERING INFORMATION

Device	Package	Shipping†
NZT660	SOT−223 (Pb−Free)	4,000 / Tape & Reel
NZT660A	SOT−223 (Pb−Free)	4,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2002

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted.)

Symbol	Parameter	Test Conditions		Min	Max	Unit
BV_{CEO}	Collector−Emitter Breakdown Voltage	I_C = −10 mA		−60	–	V
BV_{CBO}	Collector−Base Breakdown Voltage	I_C = −100 μA	NZT660	−80	–	V
			NZT660A	−60	–	
BV_{EBO}	Emitter−Base Breakdown Voltage	I_E = −100 μA		−5	–	V
I_{CBO}	Collector−Base Cut−Off Current	V_{CB} = −30 V		–	−100	nA
		V_{CB} = −30 V, T_A = 100°C		–	−10	μA
I_{EBO}	Emitter−Base Cut−Off Current	V_{EB} = −4 V		–	−100	nA
h_{FE}	DC Current Gain (Note 4)	I_C = −100 mA, V_{CE} = −2 V		70	–	
		I_C = −500 mA, V_{CE} = −2 V	NZT660	100	300	
			NZT660A	250	550	
		I_C = −1 A, V_{CE} = −2 V		80	–	
		I_C = −3 A, V_{CE} = −2 V		25	–	
V_{CE}(sat)	Collector−Emitter Saturation Voltage (Note 4)	I_C = −1 A, I_B = −100 mV		–	−300	mV
		I_C = −3 A, I_B = −300 mV	NZT660	–	−550	
			NZT660A	–	−500	
V_{BE}(sat)	Base−Emitter Saturation Voltage (Note 4)	I_C = −1 A, I_B = −100 mV		–	−1.25	V
V_{BE}(on)	Base−Emitter On Voltage (Note 4)	I_C = −1 A, V_{CE} = −2 V		–	−1	V
C_{ob}	Output Capacitance	V_{CB} = −10 V, I_E = 0, f = 1 MHz		–	45	pF
f_T	Transition Frequency	I_C = −100 mA, V_{CE} = −5 V, f = 100 MHz		75	–	MHz

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulse test: pulse width ≤ 300 μs, duty cycle ≤ 2.0%.

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. Base−Emitter Saturation Voltage vs. Collector Current




Figure 2. Base−Emitter On Voltage vs. Collector Current




Figure 3. Collector−Emitter Saturation Voltage vs. Collector Current




Figure 4. Input/Output Capacitance vs. Reverse Bias Voltage





Figure 5. Current Gain vs. Collector Current

MECHANICAL CASE OUTLINE
PACKAGE DIMENSIONS


ON Semiconductor®


SOT−223
CASE 318H
ISSUE B


DATE 13 MAY 2020



SCALE 2:1








NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSIONS D & E1 ARE DETERMINED AT DATUM H. DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. SHALL NOT EXCEED 0.23mm PER SIDE.
4. LEAD DIMENSIONS b AND b1 DO NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBBAR PROTRUSION IS 0.08mm PER SIDE.
5. DATUMS A AND B ARE DETERMINED AT DATUM H.
6. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT OF THE PACKAGE BODY.
7. POSITIONAL TOLERANCE APPLIES TO DIMENSIONS b AND b1.


	MILLIMETERS		
DIM	MIN.	NOM.	MAX.
A	---	---	1.80
A1	0.02	0.06	0.11
b	0.60	0.74	0.88
b1	2.90	3.00	3.10
c	0.24	---	0.35
D	6.30	6.50	6.70
E	6.70	7.00	7.30
E1	3.30	3.50	3.70
e	2.30 BSC		
L	0.25	---	---
θ	0°	---	10°



RECOMMENDED MOUNTING FOOTPRINT

* For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



A = Assembly Location
Y = Year
W = Work Week
XXXXX = Specific Device Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98ASH70634A**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**SOT−223**	**PAGE 1 OF 1**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2018

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Fairchild Semiconductor:

74ACQ573SCX FDB8030L FDS2672 FDS6375 FDS8928A FQPF3N80C MM74HC139N 1N4148TA
74VHC573MX FDP12N60NZ FDS6990A FQP6N90C FSL126MR H11L1M ISL9V3040P3 DM7407MX
MMBT3640 SI9936DY FCP190N60E HLMP0504 ISL9V3040S3ST KA278R12CYDTU KST42MTF
RFP12N10L SI9435DY 1N4148