- Heatsinks f.cool
- Cases f.case
- Connectors f.con
  - Sockets
  - PCB connectors
    - Male headers
    - Female headers
    - Direct female connectors
    - Jumpers
  - IDC-connectors
  - D-Sub connectors
  - Brackets for PC
  - Optoelectronics

Male headers

SL 7 ...

SL 7 17 G

Low profile

Data sheet | add to request



Features | Technical Drawing | Service | Accessories / related products

grid	2.54 mm
no. of contacts	17
contact material	CuZn-alloy
surface of contact	gold-plated
surface contact /	Ni+≥0.2µm Au
contact sleeve	Ni+4...6µm Sn
version	low profile
volume resistance	≤5 mΩ
nominal current	3 A
nominal voltage	250 V AC
test voltage	2000 V
insulating body material	PA 4.6. GF
temperature range	-40°C... +163°C (260°C/10 s)
class of inflammability	UL 94 V-0
specific insulation resistance	>10.0 $^{7.0}$ Ω·m
connection type	-
reflow solderable	yes

Fischer Elektronik GmbH & Co. KG
Nottebohmstraße 28, 58511 Lüdenscheid, DEUTSCHLAND
: +49 2351 435-0, info@fischerelektronik.de

Downloaded from Arrow.com.