OptiMOS™-5 Power-Transistor


Product Summary


V_{DS}	80	V
$R_{DS(on)}$	2.9	mΩ
I_D	165	A

Features

- N-channel - Enhancement mode
- AEC qualified
- MSL1 up to 260°C peak reflow
- 175°C operating temperature
- Green product (RoHS compliant)
- Ultra low Rds(on)
- 100% Avalanche tested

PG-HSOG-8-1





Type	Package	Marking
IAUS165N08S5N029	PG-HSOG-8-1	A08S5N29

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	T_C=25°C, V_{GS}=10V[1]	165	A
		T_C=100 °C, V_{GS}=10 V[2]	120	
Pulsed drain current[2]	$I_{D,pulse}$	T_C=25 °C	660	
Avalanche energy, single pulse[2]	E_{AS}	I_D=83 A	225	mJ
Avalanche current, single pulse	I_{AS}	-	165	A
Gate source voltage	V_{GS}	-	±20	V
Power dissipation	P_{tot}	T_C=25 °C	167	W
Operating and storage temperature	T_j, T_{stg}	-	-55 ... +175	°C
IEC climatic category; DIN IEC 68-1	-	-	55/175/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics[2]						
Thermal resistance, junction - case	R_{thJC}	-	-	-	0.9	K/W
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage[2]	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=1 mA	80	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=108 µA	2.2	3	3.8	
Zero gate voltage drain current[2]	I_{DSS}	V_{DS}=80 V, V_{GS}=0 V, T_j=25 °C	-	0.1	1	µA
		V_{DS}=50 V, V_{GS}=0 V, T_j=85 °C[2]	-	1	20	
Gate-source leakage current	I_{GSS}	V_{GS}=20 V, V_{DS}=0 V	-	-	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=6 V, I_D=40 A	-	2.9	4.4	mΩ
		V_{GS}=10 V, I_D=80 A	-	2.4	2.9	


Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics[2]						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=40 V, f=1 MHz	-	4900	6370	pF
Output capacitance	C_{oss}		-	790	1027	
Reverse transfer capacitance	C_{rss}		-	36	54	
Turn-on delay time	$t_{d(on)}$	V_{DD}=40 V, V_{GS}=10 V, I_D=100 A, R_G=3.5 Ω	-	13	-	ns
Rise time	t_r		-	9	-	
Turn-off delay time	$t_{d(off)}$		-	23	-	
Fall time	t_f		-	29	-	
Gate Charge Characteristics[2]						
Gate to source charge	Q_{gs}	V_{DD}=40 V, I_D=100 A, V_{GS}=0 to 10 V	-	24	31	nC
Gate to drain charge	Q_{gd}		-	15	23	
Gate charge total	Q_g		-	70	90	
Gate plateau voltage	$V_{plateau}$		-	5.0	-	V
Reverse Diode						
Diode continous forward current[2]	I_S	T_C=25 °C	-	-	165	A
Diode pulse current[2]	$I_{S,pulse}$		-	-	660	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=100 A, T_j=25 °C	-	0.9	1.2	V
Reverse recovery time[2]	t_{rr}	V_R=40 V, I_F=50A, di_F/dt=100 A/µs	-	60	-	ns
Reverse recovery charge[2]	Q_{rr}		-	96	-	nC

[1] Current is limited by bondwire; with an R_{thJC} = 0.9 K/W the chip is able to carry 171A at 25°C.

[2] Defined by design. Not subject to production test.


1 Power dissipation

$P_{tot} = f(T_C)$; $V_{GS} \geq 6$ V



2 Drain current


$I_D = f(T_C)$; $V_{GS} \geq 6$ V



3 Safe operating area

$I_D = f(V_{DS})$; $T_C = 25$ °C; $D = 0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJC} = f(t_p)$


parameter: $D = t_p/T$



5 Typ. output characteristics

$I_D = f(V_{DS})$; $T_j = 25$ °C


parameter: V_{GS}



6 Typ. drain-source on-state resistance

$R_{DS(on)} = (I_D)$; $T_j = 25$ °C


parameter: V_{GS}



7 Typ. transfer characteristics


$I_D = f(V_{GS})$; $V_{DS} = 6$V

parameter: T_j



8 Typ. drain-source on-state resistance


$R_{DS(on)} = f(T_j)$; $I_D = 80$ A; $V_{GS} = 10$ V



9 Typ. gate threshold voltage


$V_{GS(th)} = f(T_j)$; $V_{GS} = V_{DS}$

parameter: I_D



10 Typ. capacitances


$C = f(V_{DS})$; $V_{GS} = 0$ V; $f = 1$ MHz



11 Typical forward diode characteristicis

IF = f(V_{SD})


parameter: T_j



12 Typ. avalanche characteristics

$I_{AS} = f(t_{AV})$


parameter: $T_{j(start)}$



13 Typical avalanche energy


$E_{AS} = f(T_j)$

parameter: I_D



14 Drain-source breakdown voltage


$V_{BR(DSS)} = f(T_j)$; I_{D_typ} = 1 mA




15 Typ. gate charge

$V_{GS} = f(Q_{gate})$; I_D = 100 A pulsed

parameter: V_{DD}





Published by
Infineon Technologies AG
81726 Munich, Germany

© Infineon Technologies AG 2018
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances.
For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life.
If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Revision History

Version	Date	Changes
Version 1.0	4/10/2018	Final Data Sheet

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Infineon Technologies:

CY15V108QN-20LPXC EVALPMG1B1DRPTOBO1 IPW60R018CFD7XKSA1 IRF5210PBF IRF7853TRPBF TLE5046IC-AK-LR BSC077N12NS3 G IDH12SG60C IPF012N06NF2SATMA1 IR3895MTRPBF IRF7820TRPBF IRFS4227TRLPBF BTS 5210 G BSS126IXTSA1 IMWH170R450M1XKSA1 IPB042N10N3 G TLS4120D0EPVXUMA1 IRFP2907PBF TD340N22KOFXPSA1 IPD60R280P7S IPF010N04NF2SATMA1 IR2302STRPBF IRF3710PBF TLE6250G V33 CY8C29466-24SXIT FF800R12KE7EHPSA1 IPD60R360P7S IPT60R016CM8XTMA1 TDA21590 IPW60R070CFD7