
PJA3440-AU

40V N-Channel Enhancement Mode MOSFET

Voltage	40 V	Current	4.3A



Features

- $R_{DS(ON)}$, V_{GS}@10V, I_D@4.3A<42mΩ
- $R_{DS(ON)}$, V_{GS}@4.5V, I_D@3.9A<51mΩ
- Advanced Trench Process Technology
- Specially Designed for switch Load, PWM applications, and solid-state relays relay
- AEC-Q101 qualified
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case: SOT-23 Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0003 ounces, 0.0084 grams

Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER		SYMBOL	LIMIT	UNITS
Drain-Source Voltage		V_{DS}	40	V
Gate-Source Voltage		V_{GS}	±20	
Continuous Drain Current		I_D	4.3	A
Pulsed Drain Current (Note 4)		I_{DM}	17.2	
Power Dissipation	T_a=25°C	P_D	1.25	W
	Derate above 25°C		10	mW/°C
Operating Junction and Storage Temperature Range		T_J,T_{STG}	-55~150	°C
Typical Thermal Resistance - Junction to Ambient (Note 3)		$R_{\theta JA}$	100	°C/W

PJA3440-AU

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV_{DSS}	V_{GS}=0V, I_D=250uA	40	-	-	V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250uA	1.0	1.5	2.5	
Drain-Source On-State Resistance	$R_{DS(on)}$	V_{GS}=10V, I_D=4.3A	-	35	42	mΩ
		V_{GS}=4.5V, I_D=3.9A	-	44	51	
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=40V, V_{GS}=0V	-	-	1	uA
Gate-Source Leakage Current	I_{GSS}	V_{GS}=±20V, V_{DS}=0V	-	-	±100	nA
Dynamic (Note 5)						
Total Gate Charge	Q_g	V_{DS}=20V, I_D=4.3A, V_{GS}=4.5V (Note 1,2)	-	4.8	-	nC
Gate-Source Charge	Q_{gs}		-	1.4	-	
Gate-Drain Charge	Q_{gd}		-	1.8	-	
Input Capacitance	Ciss	V_{DS}=20V, V_{GS}=0V, f=1.0MHZ	-	410	-	pF
Output Capacitance	Coss		-	50	-	
Reverse Transfer Capacitance	Crss		-	30	-	
Turn-On Delay Time	$td_{(on)}$	V_{DD}=20V, I_D=3.5A, V_{GS}=10V, R_G=1Ω (Note 1,2)	-	4	-	ns
Turn-On Rise Time	tr		-	30	-	
Turn-Off Delay Time	$td_{(off)}$		-	15	-	
Turn-Off Fall Time	tf		-	8	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I_S	---	-	-	1.0	A
Diode Forward Voltage	V_{SD}	I_S=1.0A, V_{GS}=0V	-	0.78	1.2	V
Reverse Recovery Time	trr	V_{GS}=0V, I_S=3.5A dI_F/ dt=100A/us	-	10.2	-	ns
Reverse Recovery Charge	Qrr		-	5.5	-	nC

NOTES :

1. Pulse width≤300us, Duty cycle≤2%.
2. Essentially independent of operating temperature typical characteristics.
3. $R_{\Theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins mounted on a 1 inch FR-4 with 2oz. square pad of copper.
4. The maximum current rating is package limited.
5. Guaranteed by design, not subject to production testing.

PJA3440-AU

TYPICAL CHARACTERISTIC CURVES




Fig.1 On-Region Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 On-Resistance Variation with V_{GS}




Fig.6 Body Diode Characteristics

PJA3440-AU

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Threshold Voltage Variation with Temperature





Fig.9 Capacitance vs. Drain-Source Voltage

PJA3440-AU

Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type	Marking	Version
PJA3440-AU_R1_000A1	SOT-23	3K pcs / 7” reel	A40	Halogen free

Mounting Pad Layout



PJA3440-AU

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

PANJIT:

MMSZ5248B_R1_00001 S100_R1_00001 BAT750_R1_00001 BAV99_R1_00001 ER2004CT_TO_00001
MMSZ5242B_R1_00001 P4FL6.5A_R1_00001 ZMM55-C43_R1_10001 P6SMB75A_R3_00001
S1G_R2_00001 SB34AFC-AU_R1_000A1 UF808_T0_00001 GS1M_R1_10001 SB34AFC_R1_00001
SB36AFC-AU_R1_000A1 PJSD24TS-AU_R1_000A1 PSDB1560L1_T0_00001 PSDH6060CCS1_T0_00001
S3JA_R2_00001 BAV70_R1_00101 BZT52-B27S GS1010FL-LE_R1_00001 BZT52-B8V2S_R1_00001
BZT52B12S_R1_00001 P4SMAJ180A_R1_00001 ER2D_R2_00001 P6SMBJ10A_R1_00001
SS20100FL_R1_00001 BSS8402DW_R1_00001 MMSZ5245AS_R1_00001