Manual override
AHB-MEB

Part number: 157601



General operating condition

Data sheet

Feature	Value
Mounting position	Any
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Ambient temperature	-5 °C ... 60 °C
Type of mounting	Engaging
Housing material	PA6-reinforced

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

HGL-1/8-QS-6 NPQP-LQ-R18-Q8-FD-P10 QSF-3/8-8-B QSY-6H-4 153269 NPQP-D-Q4-S8-FD-P10 NPQP-Y-R12-Q12-FD QSS-8-F SASC-P4-A-M8-A QS-10H-6 NPQP-T-Q8-E-FD-P10 NPQH-T-Q14-E-P10 NPQP-L-Q10-E-FD-P10 NPQP-LQ-R18-Q4-FD-P10 VBQF-U-G14-E DSBC-80-20-D3-PPSA-N3 153307 NPQP-Y-Q6-E-FD-P10 CRVZS-0.4 VABM-B10-25S-G38-6-P3 QS-1/2-16 QS-1/8-8-I QSF-1/4-8-B QSLL-G1/2-12 QSML-6 153031 153151 153367 SGS-M10X1,25 VABM-B10-25S-G38-10