HPESD3V3S1BA
ESD PROTECTION DIODE

Discription

Low capacitance bidirectional ElectroStatic Discharge (ESD) protection diode in a ultra-small and flat lead SOD-523 plastic package designed to protect one signal line from the damage caused by ESD and other transients.



SOD-523

Features

- ★ Ultra Low Capacitance 15 pF(Typ)
- ★ Reverse stand-off voltage: 3.3V Max
- ★ Low leakage current: nA Level
- ★ Response time is typically < 1 ns
- ★ IEC61000-4-2 Level 4 ESD Protection



Circuit Diagram

Applications

- ★ High- speed data lines
- ★ Smart phones
- ★ Display Ports
- ★ MDDI Ports
- ★ USB Ports
- ★ Digital Video Interface (DVI)
- ★ PCI Express and Serial SATA Ports

Orderingin formation

Product ID	Pack	Qty(PCS)
HPESD3V3S1BA	SOT-523	3000


Absolute Ratings(Tamb = 25°C)

Parameter	Symbol	Value	Unit
Peak Pulse Power (tp = 8/20μs)	P_{PPM}	100	W
Peak Pulse Current(tp = 8/20μs)	I_{PPM}	9	A
Maximum lead temperature for soldering during 10s	T_L	260	°C
Storage Temperature Range	T_{stg}	-55 to +150	°C
Operating Temperature Range	T_{OP}	-40 to +125	°C
ESD voltage IEC 61000-4-2 (air discharge)	V_{ESD}	15	kV
ESD voltage IEC 61000-4-2 (contact discharge)	V_{ESD}	8	kV


Electrical Characteristics

Parameter	Symbol	Min	Typ	Max	Unit	Condition
Reverse Working Voltage	V_{RWM}	--	--	3.3	V	
Breakdown Voltage	V_{BR}	5.6	--	7.8	V	I_T=1mA
Leakage Current ILeak	I_R	--	--	1.0	uA	V_{RWM}=5V
Clamping Voltage	V_C	--	--	11.0	V	I_{PP}=4A,Tp=8/20μs
Junction Capacitance	C_J	--	15	--	pF	V_R=0V, f=1MHz

Typical Characteristics




IEC61000−4−2 Waveform




IEC 61000-4-5 Waveform(8/20μs pulse)


Outline And Dimensions



TOP VIEW



SIDE VIEW




BOTTOM VIEW

Notes:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.

	MILLIMETERS			INCHES		
DIM	MIN	NOM	MAX	MIN	NOM	MAX
A	0.50	0.60	0.70	0.020	0.024	0.028
b	0.25	0.30	0.35	0.010	0.012	0.014
c	0.07	0.14	0.20	0.003	0.006	0.008
D	1.10	1.20	1.30	0.043	0.047	0.051
E	0.70	0.80	0.90	0.028	0.031	0.035
H_E	1.50	1.60	1.70	0.059	0.063	0.067
L	0.30 REF			0.012 REF		
L_2	0.15	0.20	0.25	0.006	0.008	0.010

Soledering Footprint



DIMENSION: MILLIMETERS

Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

HXY MOSFET:

IRLML2244TRPBF-HXY IPD042P03L3G SMAJ17A SMAJ6.5CA MMBT3904 AMS1117-3.3V 60N06 CSD17308Q3 IRLML6244TRPBF TPD1E0B04DPYR BC847C MMDT5551 BZT52C36 SFT1342 BAT43W SMBJ28CA HXY30G20DF TLV74318PDBVR-HXY HUDD32C12L01 2SC1623 SS510C SI4435DYPBF FDV301N FDS6930B HXY4266S ADP151AUJZ-3.3-R7 BZX84C3V3 Si2323DS-T1-E3-HXY USBLC6-2SC6 SD05