TECH PUBLIC
台舟电子

PDFB033250-SOD923

1-Line Bi-directional Diode

www.sot23.com.tw

Features

- Ultra low capacitance: 12pF typical
- Ultra low leakage: nA level
- Low operating voltage: ±3.3V
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
- – IEC 61000-4-2 (ESD) immunity test
  Air discharge: ±30kV
  Contact discharge: ±30kV
- – IEC61000-4-5 (Lightning)8A (8/20μs)
- RoHS Compliant
- Lead Finish: NiPdAu


Mechanical Characteristics

- Package: SOD-923 (0402)
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Terminal Connections: See Diagram Below
- Shipping Qty :8000pcs/7Inch Tape & Reel

Applications

- Smart Phone and Tablet PC
- TV and Set Top Box
- Wearable Devices
- PDA

Dimensions and Pin Configuration



SOD923

Absolute Maximum Ratings (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	Ppk	100	W
Peak Pulse Current (8/20μs)	Ipp	8	A
ESD per IEC 61000−4−2 (Air) ESD per IEC 61000−4−2 (Contact)	V_{ESD}	±30 ±30	kV
Operating Temperature Range	T_J	−55 to +125	°C
Storage Temperature Range	Tstg	−55 to +150	°C

Electrical Characteristics (TA=25°C unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V_{RWM}			3.3	V	
Breakdown Voltage	V_{BR}	3.6			V	I_T = 1mA
Reverse Leakage Current	I_R			0.08	uA	V_{RWM} = 3.3V
Clamping Voltage	V_C			6	V	Ipp=1A(8x 20us pulse)
Clamping Voltage	V_C			10	V	Ipp=8A(8x 20us pulse)
Junction Capacitance	C_J		12	18	pF	VR = 0V, f = 1MHz

Characteristic Curves

Fig1. 8/20μs Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)






Fig3. Power Derating Curve




Outline Drawing - SOD-923(0402)



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.037	.041	0.95	1.05	
B	.030	.033	0.75	0.85	
C	.022	.026	0.55	0.65	
D	.014	.017	0.36	0.43	
E	.006	.010	0.15	0.25	
F	.003	.007	0.07	0.17	

Land Pattern - SOD-923(0402)



Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

TECH PUBLIC:

BV15C SI3932DV TPDMG6602SVT TPS3809L30DBVR-TP TPZVN3320FTA TPZXMP3A13FTA DDTA143ZCA FDC6301N-TP DMP6350S QM3003J-TP TPD1213A-02SM TPESD0402G08V TPESD0504S6-A TPS7B6950DBVR-TP TPADM809SAKSZ TPESD5311N TPGC12C-1 TPADM809LAKSZ TPAPX809S-31SA TPFMMT493 TPWSB5557Z ESD5B5.0ST1G-P TPB05A40-323 BSN20W FDMS7670AS-TP IRFR2405TRPBF-TP LTH7 TPB1A30-123 SN7002W TPSPX3819M5-L-3-3