






Keying Shown as example



LAYOUT SHOWN AS EXAMPLE

CHARACTERISTICS

-Standard : Based on MIL-DTL-38999 Series III
-Shell Material : Aluminium
-Shell Plating : Olive drab Cadmium
-Insulator : Thermoplastic
-Contacts : Copper Alloy
-Seals & Grommet : Silicon Elastomer
-Contact Plating : Gold over copper Alloy 0.8µm minimum
-Durability : 500 Mating cycles
-Delivered with Souriau contacts and Accessories

-Temperature Range : -65°C to +175°C
-Salt Spray : 500 hours
-Mass : 82.14 g ± 10%

Connector dimension	
Dim	**Nominal**
P	3.91±0.2
PP	6.15±0.2
R1	38.1
R2	34.93
S	46±0.3
V	20.07+0/-1.25
W	2.1/3.2
Z	31.5 Max
VV THREAD	M37x1-6g

BASIC SERIES:	8D	0	-	25	W	43	B	D	
SHELL TYPE : Square Flange Receptacle									
CONTACT TYPE : Standard Crimp Contact									ORIENTATION : D
SHELL SIZE : 25									CONTACT TYPE : SOCKET(500 Matings)
PLATING : W = Olive drab Cadmium									CONTACT LAYOUT : 25-43

SOURIAU shall not be liable for any non-conformity or damage
due to a use of the Products which does not comply with
the Specifications issued by either of the Parties or by a third party
(professional recommendation, technical notice.)

Country	Jurisdiction & Control List
FR	Not Listed

PN: 8D025W43BD

ISS	DATE	Latest modification - by	MOD N°
A	08-10-2016	First Release	

Designed By: Date: **CUSTOMER DRAWING**


TITLE Aluminium Receptacle 8D series

SCALE NA | General linear Tolerances: ±-- | NPRDS / PROJECT **859**

SOURIAU | WWW.SOURIAU.COM | This document is the property of SOURIAU
it must not be reproduced or
communicated without permission

FORMAT A3 | SOURIAU DRG N° 8D025W43BD-C | SHEET 1/2


Contact Layout



Contacts (Insert arrangement 25-43)					
Contact position ID	Location X-axis (mm)	Location Y-axis (mm)	Contact position ID	Location X-axis (mm)	Location Y-axis (mm)
A	+.069 (1.75)	+.531 (13.49)	Z	-.069 (1.75)	+.531 (13.49)
B	+.203 (5.16)	+.495 (12.57)	a	+.172 (4.37)	+.344 (8.74)
C	+.324 (8.23)	+.425 (10.80)	b	+.258 (6.55)	+.172 (4.37)
D	+.424 (10.77)	+.326 (8.28)	c	+.344 (8.74)	+.000 (0.00)
E	+.493 (12.52)	+.205 (5.21)	d	+.344 (8.74)	-.172 (4.37)
F	+.531 (13.49)	+.069 (1.75)	e	+.172 (4.37)	-.344 (8.74)
G	+.531 (13.49)	-.069 (1.75)	f	+.000 (0.00)	-.344 (8.74)
H	+.493 (12.52)	-.205 (5.21)	g	-.172 (4.37)	-.344 (8.74)
J	+.424 (10.77)	-.326 (8.28)	h	-.344 (8.74)	-.172 (4.37)
K	+.324 (8.23)	-.425 (10.80)	k	-.344 (8.74)	+.000 (0.00)
L	+.203 (5.16)	-.495 (12.57)	m	-.258 (6.55)	+.172 (4.37)
M	+.000 (0.00)	-.531 (13.49)	n	-.172 (4.37)	+.344 (8.74)
N	-.203 (5.16)	-.495 (12.57)	p	+.000 (0.00)	+.344 (8.74)
P	-.324 (8.23)	-.425 (10.80)	q	+.086 (2.18)	+.172 (4.37)
R	-.424 (10.77)	-.326 (8.28)	r	+.172 (4.37)	+.000 (0.00)
S	-.493 (12.52)	-.205 (5.21)	s	+.172 (4.37)	-.172 (4.37)
T	-.531 (13.49)	-.069 (1.75)	t	+.000 (0.00)	-.172 (4.37)
U	-.531 (13.49)	+.069 (1.75)	u	-.172 (4.37)	-.172 (4.37)
V	-.493 (12.52)	+.205 (5.21)	v	-.172 (4.37)	+.000 (0.00)
W	-.424 (10.77)	+.326 (8.28)	w	-.086 (2.18)	+.172 (4.37)
X	-.324 (8.23)	+.425 (10.80)	x	+.000 (0.00)	+.000 (0.00)
Y	-.203 (5.16)	+.495 (12.57)			

Shell size	Arrangement no.	Number of contacts	Size contacts	Service rating	Contact location	Supersedes
25	-43	20	16	I	a,b,c,d,e,f,g,h,k,m,n,p,q,r,s,t,u,v,w,x	MS20057-43
		23	20		All others	

Panel Cutout



Dim	Nominal
ØA	42.47 min
ØAA	37.69 min
R1	38.1
ØT	3.81 ±0.13

SOURIAU shall not be liable for any non-conformity or damage
due to a use of the Products which does not comply with
the Specifications issued by either of the Parties or by a third party
(professional recommendation, technical notice.)

Country	Jurisdiction & Control List
FR	Not Listed

PN: 8D025W43BD

ISS	DATE	Latest modification - by	MOD N°
A	08-10-2016	First Release	

Designed By: Date: **CUSTOMER DRAWING**

TITLE Aluminium Receptacle 8D series

SCALE NA

General linear Tolerances: ±--

NPRDS / PROJECT **859**

SOURIAU WWW.SOURIAU.COM

This document is the property of SOURIAU
it must not be reproduced or communicated without permission

FORMAT A3

SOURIAU DRG N° 8D025W43BD-C

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

Souriau-Sunbank:

UTL6122G1W5P SC24ML-1D70 8MQ2M01L28ADE 8MQ2M1220AD UTGX71419P UTS6JC1823S
D38999/26JJ24PN D38999/26MJ24PN-LC UT010LPGN UT0S16JCS UTG22PG 8MQ2M0412RCE
SC20WL-3S25 UTG11412PH 8MQ2M0412ABE 8MQ2M0412PB SM16ML-1S6 UT061619SH
UTS6JC1823P UTP14DCG UTS08E3P 8D525M24PN RM28M1K UT001412SH UTGX1JC103P
SC24WL-3S25 UTS10DCGE 8MQ2M0816BCE BIS10PLN0416M UTSX0128P