
Barb tubing fitting
C-3/8-P-9

Part number: 2025



General operating condition

Data sheet

Feature	Value
Nominal width	6.5 mm
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:-]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Pneumatic connection 1	Internal thread G3/8
Pneumatic connection 2	for pneumatic tubing inside diameter 9 mm

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

FESTO:

DSBC-80-320-D3-PPVA-N3 NPQP-LQ-R18-Q4-FD-P10 QSLV-G1/4-6 QSS-8-F NPQP-L-Q10-E-FD-P10 DSBC-80-250-D3-PPSA-N3 DSNU-12-60-P-A NPQP-Y-Q6-E-FD-P10 QSLL-1/4-4 QS-1/2-16 VBQF-U-G14-E DFM-63-100-P-A-KF DSBC-32-40-D3-PPVA-N3 DSBC-63-320-D3-PPVA-N3 N-1/8-P-6 NPQP-D-Q4-S8-FD-P10 DSBC-32-50-D3-PPVA-N3 DSBC-50-20-D3-PPSA-N3 MSFW-110-50/60-DS NPQH-T-G38-Q8-P10 QSML-3 SNC-63 VABM-L1-18W-G38-8-G CRVZS-0.4 NPQP-LQ-R18-Q8-FD-P10 NPQP-Y-R12-Q12-FD QH-1 1/2 QSML-6 SPTE-V1R-Q3-V-2.5K PUN-H-4X0,75-TBL