
P-Channel Enhancement Mode Power MOSFET

30V P-Channel MOSFET

$V_{(BR)DSS}$	$R_{DS(on)}$MAX	I_D
-30V	0.012Ω@-10V	-34 A
	0.020Ω@ -5.0V	

PDFN5X6-8L



General FEATURE

- Tower MOSFET
- Lead free product is acquired
- Surface mount package

APPLICATION

- Load Switch for Portable Devices
- DC/DC Converter

Absolute Maximum Ratings T_A=25℃ unless otherwise noted				
Parameter		**Symbol**	**Maximum**	**Units**
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	±25	V
Continuous Drain Current	T_C=25℃	I_D	-34	A
	T_C=100℃		-21.5	
Pulsed Drain Current [C]		I_{DM}	-95	
Continuous Drain Current	T_A=25℃	I_{DSM}	-12	A
	T_A=70℃		-10	
Avalanche Current [C]		I_{AS}	24	A
Avalanche energy L=0.1mH [C]		E_{AS}	29	mJ
Power Dissipation [B]	T_C=25℃	P_D	31	W
	T_C=100℃		12.5	
Power Dissipation [A]	T_A=25℃	P_{DSM}	4.1	W
	T_A=70℃		2.6	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	℃

Thermal Characteristics					
Parameter		**Symbol**	**Typ**	**Max**	**Units**
Maximum Junction-to-Ambient [A]	t ≤ 10s	$R_{\theta JA}$	24	30	℃/W
Maximum Junction-to-Ambient [A D]	Steady-State		53	64	℃/W
Maximum Junction-to-Case	Steady-State	$R_{\theta JC}$	3.4	4	℃/W

Electrical Characteristics (T_J=25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250μA, V_{GS}=0V	-30			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-30V, V_{GS}=0V			-1	μA
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±25V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=$V_{GS,}$ I_D=-250μA	-1.7	-2.3	-3	V
$I_{D(ON)}$	On state drain current	V_{GS}=-10V, V_{DS}=-5V	-95			A
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-10V, I_D=-20A		12	15	mΩ
		V_{GS}=-5V, I_D=-15A		20	25	Ω
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-20A		28		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V		-0.73	-1	V
I_S	Maximum Body-Diode Continuous Current				-35	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-15V, f=1MHz		1130	1400	pF
C_{oss}	Output Capacitance			240		pF
C_{rss}	Reverse Transfer Capacitance			155		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		5.8	8	Ω
SWITCHING PARAMETERS						
Q_g(10V)	Total Gate Charge	V_{GS}=-10V, V_{DS}=-15V, I_D=-20A		21		nC
Q_g(4.5V)	Total Gate Charge			10		nC
Q_{gs}	Gate Source Charge			4		nC
Q_{gd}	Gate Drain Charge			6		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-10V, V_{DS}=-15V, R_L=0.75Ω, R_{GEN}=3Ω		10		ns
t_r	Turn-On Rise Time			8		ns
$t_{D(off)}$	Turn-Off DelayTime			15		ns
t_f	Turn-Off Fall Time			7		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-20A, dI/dt=500A/μs		13.5		ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-20A, dI/dt=500A/μs		29		nC

A. The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with T_A =25° C. The Power dissipation P_{DSM} is based on $R_{\theta JA}$ and the maximum allowed junction temperature of 150° C. The value in any given application depends on the user's specific board design, and the maximum temperature of 150° C may be used if the PCB allows it.

B. The power dissipation P_D is based on $T_{J(MAX)}$=150° C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.

C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150° C. Ratings are based on low frequency and duty cycles to keep initial T_J =25° C.Maximum UIS current limited by test equipment.

D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.

E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=150° C. The SOA curve provides a single pulse rating.

G. The maximum current rating is package limited.

H. These tests are performed with the device mounted on 1 in² FR-4 board with 2oz. Copper, in a still air environment with T_A=25° C.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics (Note E)




Figure 2: Transfer Characteristics (Note E)




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note F)




Figure 10: Single Pulse Power Rating Junction-to-Case (Note F)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 12: Single Pulse Avalanche capability (Note C)




Figure 13: Power De-rating (Note F)




Figure 14: Current De-rating (Note F)




Figure 15: Maximum Forward Biased Safe Operating Area (Note H)







Figure 16: Single Pulse Power Rating Junction-to-Ambient (Note H)


Gate Charge Test Circuit & Waveform







Resistive Switching Test Circuit & Waveforms







Unclamped Inductive Switching (UIS) Test Circuit & Waveforms







Diode Recovery Test Circuit & Waveforms






PDFNWB5x6-8L Package Outline Dimensions








Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	3.910	4.110	0.154	0.162
E1	3.375	3.575	0.133	0.141
D2	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°

PDFNWB5x6-8L Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

JSMICRO:

2SK1591 2SK4033 ESD8D12W JSM8810 MC78L05ABDR2G 2SK2978 BZT52C36SQ BSC018N04LSGATMA1 BZT52C47Q C2M0040120D FMMT619TC 2SK1586 AZ1045-04F BZT52C43SQ GBU1510 PESD2510Q12 TPS1100DRG4 2SK1133-T1B-A 2SK2931 XP202A0003PR 2ED2304S06F 2SK2926 LMUN2116LT1G 2SK1284 ESD0501CU ESD0501OC 2SK3878 C2M0045170P JSM7409B PESD1CAN-UX