Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Date of issue 12/09/2025 Version number 5.00 Revision: 12/09/2025

1 Identification

· **Product identifier**

· **Trade name: 834FX-A**

· **Other Means of Identification:** Black Flexible Epoxy (Part A)

· **Related Part Number:** 834FX-Part A, 834FX-450ML, 834FX-1.7L, 834FX-7.4L, 834FX-40L

· **Application of the substance / the mixture** Epoxy resin

· **Uses advised against** Not applicable

· **Details of the supplier of the safety data sheet**

·

Manufacturer/Supplier:
MG Chemicals (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA
+(1) 800-340-0772
+(1) 905-331-1396
info@mgchemicals.com

·

Distributor:
Masline
511 Clinton Ave S
Rochester, New York 14620
United States
+(1) 586-546-5373

· **Information department:** sds@mgchemicals.com

· **Emergency telephone number:**

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA-Call 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

* 2 Hazard identification

· **Classification of the substance or mixture**

Acute Toxicity (Oral) - Category 4	H302 Harmful if swallowed.
Skin Irritation - Category 2	H315 Causes skin irritation.
Eye damage/irritation – Category 2A	H319 Causes serious eye irritation.
Sensitization - skin – Category 1	H317 May cause an allergic skin reaction.
Reproductive Toxicity - Category 2	H361 Suspected of damaging fertility or the unborn child.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

(Contd. of page 1)

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**
propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers
polyglycol, epichlorohydrin polymer
boron zinc hydroxide oxide
Carbon black

· **Hazard statements**
H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing fumes and vapors.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing, and eye protection.
P301+P312	IF SWALLOWED: Call a POISON CENTER if you feel unwell.
P330	Rinse mouth.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice.
P333+P313	If skin irritation or rash occurs: Get medical advice.
P337+P313	If eye irritation persists: Get medical advice.
P362+P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents and container in accordance with local, regional, and national regulations.

· **Other hazards** Not available

(Contd. on page 3)

(Contd. of page 2)

3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**
· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**		
21645-51-2	aluminium hydroxide	22.0% w/w
25085-99-8	propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	22.0% w/w
68333-79-9	Ammonium Polyphosphate	19.0% w/w
1344-28-1	aluminium oxide	14.0% w/w
41638-13-5	polyglycol, epichlorohydrin polymer	8.0% w/w
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	7.0% w/w
138265-88-0	boron zinc hydroxide oxide	5.0% w/w
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Alternative CAS number: 1675-54-3	1.0% w/w
68037-01-4	1-Decene, homopolymer, hydrogenated	0.6% w/w
1333-86-4	Carbon black	0.4% w/w
64741-65-7	Naphtha (petroleum), heavy alkylate	0.4% w/w

4 First-aid measures

· **Description of first aid measures**
· **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
· **After inhalation:**
Remove person to fresh air and keep comfortable for breathing.
If feeling unwell: Call a POISON CENTRE or doctor.
· **After skin contact:**
Wash with plenty water.
If skin irritation or rash occurs: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.
If exposed or concerned: Get medical advice or attention.
· **After eye contact:**
Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice or attention.
· **After swallowing:**
Call a POISON CENTER/doctor if you feel unwell.
Rinse mouth.
Do NOT induce vomiting.
If exposed or concerned: Get medical advice or attention.

· **Most important symptoms and effects, both acute and delayed**
See section 11 for additional information.

(Contd. on page 4)

(Contd. of page 3)

· **Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

5 Fire-fighting measures

· **Extinguishing media**
· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

· **Special hazards arising from the substance or mixture**
The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure.
Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.
Prevent fire-fighting wash from entering waterway or sewer system.
Inhalation of metal fumes may cause metal fever and irritate the respiratory tract.
· **Hazardous combustion products:**
Carbon Oxides (COx)
Boron oxides
other toxic fumes

· **Advice for firefighters**
· **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**
Avoid breathing the fumes or vapors.
Remove or keep away all sources of extreme heat or open flames.

· **Environmental precautions:**
Avoid release to the environment.
Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Collect liquid in a sealable, chemical-resistant container.
Wash residue with a paper towel and place dirty towels in container.
Use soap and water to remove the last traces of residue.

· **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 5)

(Contd. of page 4)

7 Handling and storage

· **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Wear protective gloves and eye protection.
Wash hands and exposed skin thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Collect spillage.
Contaminated work clothing should not be allowed out of the workplace.
Obtain, read and follow all safety instructions before use.
Do not eat, drink, or smoke when using this product.

· **Information about protection against explosions and fires:**
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**
Keep in a dry and clean area, away from incompatible substances

· **Information about storage in one common storage facility:** Not required

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** See section 1.2

8 Exposure controls/ Personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**	
1333-86-4 Carbon black	
EL (Canada)	TWA: 3 mg/m³ IARC 2B
EV (Canada)	TWA: 3.5 mg/m³
PEL (USA)	TWA: 3.5 mg/m³
REL (USA)	TWA: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C
TLV (USA)	TWA: 3* mg/m³ *inhalable fraction, A3

· **Additional information:**
The lists that were valid during the creation were used as basis.
Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

· **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Personal protective equipment:**

· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.

(Contd. on page 6)

(Contd. of page 5)

Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Breathing equipment:**
If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

· **Protection of hands:**
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses or tightly sealed goggles: EN 166

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Physical state**	Liquid
· **Form:**	Highly viscous
· **Color:**	Black
· **Odor:**	Mild
· **Odor threshold:**	Not determined
· **Melting point/Melting range:**	Undetermined
· **Boiling point/Boiling range:**	≥218 °C (≥424.4 °F)
· **Flammability:**	Non flammable
· **Explosion limits:**	
· **Lower:**	Not applicable
· **Upper:**	Not applicable
· **Flash point:**	>150 °C (>302 °F)
· **Auto igniting:**	Not determined

(Contd. on page 7)

(Contd. of page 6)

· **Decomposition temperature:**	Not determined
· **pH-value:**	Not determined
· **Viscosity:**	
· **Kinematic at 25 °C (77 °F):**	4566 cP
· **Dynamic:**	Not determined
· **Solubility in / Miscibility with**	
· **Water:**	Not miscible or difficult to mix.
· **Partition coefficient (n-octanol/water):**	Not determined
· **Vapor pressure:**	Not determined
· **Relative density at 25 °C (77 °F):**	1.63
· **Vapor density (air=1):**	Not determined
· **Particle characteristics**	Not applicable

· **Other information**

· **Important information on protection of health and environment, and on safety.**	
· **Ignition temperature:**	Product is not selfigniting.
· **Danger of explosion:**	Product does not present an explosion hazard.
· **Organic solvents:**	Not available
· **VOC content:**	0.000 % 0.0 g/l / 0.00 lb/gal
· **Solids content:**	37.0 %
· **Evaporation rate**	Not determined

10 Stability and reactivity

· **Reactivity** Reacts exothermically with amines.

· **Chemical stability** Chemically stable at normal temperatures and pressures.

· **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** Avoid ignition sources, open flames, and incompatible substances.

· **Incompatible materials:**
alkali
Strong oxidizing agents
Strong acids

· **Hazardous decomposition products:**
No dangerous decomposition products known.
Hazardous combustion products: see section 5.

(Contd. on page 8)

(Contd. of page 7)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**		
ATE (Acute Toxicity Estimate)		
Oral	LD50	2,632 mg/kg

21645-51-2 aluminium hydroxide		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	mg/L (rat)
25085-99-8 propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers		
Dermal	LD50	23,000 mg/kg (rabbit)
68333-79-9 Ammonium Polyphosphate		
Oral	LD50	500 mg/kg (ATE)
1344-28-1 aluminium oxide		
Oral	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>2 mg/L (mouse)
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Oral	LD50	19,200 mg/kg (rat)
Dermal	LD50	4,500 mg/kg (rat)
138265-88-0 boron zinc hydroxide oxide		
Oral	LD50	>10,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rat)
25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)		
Oral	LD50	11,400 mg/kg (rat)
68037-01-4 1-Decene, homopolymer, hydrogenated		
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.2 mg/L (rat)
1333-86-4 Carbon black		
Oral	LD50	>15,400 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rabbit)
64741-65-7 Naphtha (petroleum), heavy alkylate		
Oral	LD50	>6,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>7.8 mg/L (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 9)

(Contd. of page 8)

· **Summary of effects and symptoms by route of exposure**
· **Eyes:** redness, serious irritation
· **Skin:**
rash, allergic contact dermatitis
redness, irritation
· **Inhalation:** cough
· **Swallowed:** irritation to the mouth, throat, esophagus, and stomach

· **Delayed and immediate effects as well as chronic effects from short and long-term exposure**
Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

· **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**		
1333-86-4	Carbon black	2B

· **NTP (National Toxicology Program)**
None of the ingredients is listed.

12 Ecological information

· **Toxicity**
· **Aquatic toxicity:**
Toxic to aquatic life with long lasting effects.
Avoid release to the environment.
Collect spillage.

25085-99-8 propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	
LC50 96h	>1 mg/L (N/Av)
138265-88-0 boron zinc hydroxide oxide	
LC50 96h	2.4 mg/L (trout)
LC50/ 48 h	76 mg/L (daphnia)
1333-86-4 Carbon black	
EC50/ 24 h	>5,600 mg/L (aquatic invertebrates)
EC50/ 72 h	>10,000 mg/L (aquatic algae and cyanobacteria)
EC0/ 3 h	>800 mg/L (microorganisms)
LC50	>1,000 mg/L (fish)

· **Persistence and degradability** No further relevant information available.

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

(Contd. on page 10)

(Contd. of page 9)

· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

· **Other adverse effects**
· **Remark:** Toxic for fish

13 Disposal considerations

· **Waste treatment methods**
· **Recommendation:** This material and its container must be disposed of as hazardous waste.

· **Uncleaned packagings:**
· **Recommendation:**
Containers may still present a chemical hazard/ danger when empty.
Dispose of contents in accordance with all local, regional, national, and international regulations.
Where possible retain label warnings and SDS and observe all notices pertaining to the product.

14 Transport information

· **UN-Number**	
· **DOT/TDG, IMDG, IATA**	UN3082
· **UN proper shipping name**	
· **DOT/TDG**	Environmentally hazardous substance, liquid, n.o.s. (propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers, boron zinc hydroxide oxide)
· **IMDG**	NOT REGULATED by Sea IMDG per 2.10.2.7 for sizes 5L or less. ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (propane, 2,2-bis[p-(2,3-epoxypropoxy) phenyl]-, polymers, zinc borate), MARINE POLLUTANT
· **IATA**	NOT REGULATED by Air IATA Special Provision A197 for sizes 5L or less. Environmentally hazardous substance, liquid, n.o.s. (propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers, zinc borate)

(Contd. on page 11)

(Contd. of page 10)

· **Transport hazard class(es)**

· **DOT/TDG, IATA**



· **Class** 9 Miscellaneous dangerous substances and articles
· **Label** 9

· **IMDG**



· **Class** 9 Miscellaneous dangerous substances and articles
· **Label** 9

· **Packing group**
· **DOT/TDG, IMDG, IATA** III

· **Environmental hazards:**
· **Marine pollutant:** MARINE POLLUTANT
· **Special marking (IATA):** ENVIRONMENTALLY HAZARDOUS
Symbol (fish and tree)

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable

· **Transport/Additional information:**

· **DOT/TDG**
· **Quantity limitations** On passenger aircraft/rail: 450 L
On cargo aircraft only: 450 L
· **Remarks:** Special marking with the symbol (fish and tree).

· **IMDG**
· **Limited quantities (LQ)** 5L
· **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· **Special precautions for user** Not applicable
· **Hazard identification number (Kemler code):** 90
· **EMS Number:** F-A,S-F
· **Stowage Category** A

(Contd. on page 12)

(Contd. of page 11)

· **UN "Model Regulation":**	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PROPANE, 2,2-BIS[P-(2,3-EPOXYPROPOXY)PHENYL]-, POLYMERS, ZINC BORATE), 9, III

* 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **OSHA Hazard Communication Standard (29 CFR Part 1900)**
The safety data sheet and label comply with HCS 2024.

· **Hazardous Products Act (R.S.C., 1985, c. H-3)**
The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

· **Sara**

· **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**	
1344-28-1	aluminium oxide

· **TSCA (Toxic Substances Control Act):**		
21645-51-2	aluminium hydroxide	ACTIVE
25085-99-8	propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	ACTIVE
68333-79-9	Ammonium Polyphosphate	ACTIVE
1344-28-1	aluminium oxide	ACTIVE
41638-13-5	polyglycol, epichlorohydrin polymer	ACTIVE
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	ACTIVE
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	ACTIVE
68037-01-4	1-Decene, homopolymer, hydrogenated	ACTIVE
1333-86-4	Carbon black	ACTIVE

· **Hazardous Air Pollutants**
None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**	
1333-86-4	Carbon black

· **Chemicals known to cause reproductive toxicity for females:**
None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**
None of the ingredients is listed.

(Contd. on page 13)

(Contd. of page 12)

· **Chemicals known to cause developmental toxicity:**
None of the ingredients is listed.

· **Carcinogenic categories**

· **TLV (Threshold Limit Value)**		
1344-28-1	aluminium oxide	A4
1333-86-4	Carbon black	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**	
1333-86-4	Carbon black

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**	
21645-51-2	aluminium hydroxide
25085-99-8	propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers
68333-79-9	Ammonium Polyphosphate
1344-28-1	aluminium oxide
41638-13-5	polyglycol, epichlorohydrin polymer
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
68037-01-4	1-Decene, homopolymer, hydrogenated
1333-86-4	Carbon black
64741-65-7	Naphtha (petroleum), heavy alkylate

· **Canadian Non-Domestic Substances List (NDSL)**
None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**
None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**	
1344-28-1	aluminium oxide

· **HMIS-ratings (scale 0 - 4)**
Health = * 2
Fire = 1
Reactivity = 0

· **Europe**

· **RoHS (Restriction of Hazardous Substances Directive)**
This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

· **WEEE (Waste Electrical and Electronic Equipment Directive)**
This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

(Contd. on page 14)

(Contd. of page 13)

· **Per- and polyfluoroalkyl substances (PFAS)**
None of the ingredients is listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Regulatory department
· **Contact:** sds@mgchemicals.com
· **Version number of previous version:** 4.01
· **Date of preparation** 12/09/2025
· **Abbreviations and acronyms:**
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
· *** Data compared to the previous version altered.**