



REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-8B0071	2008/09/25	Shin	Add Note
C	LEN15A0328	2015/06/04	Jinhai	Change Logo
D	C190271	2019/03/04	Ruru	Modify Note

ALTW
CONFIDENTIAL
2019-03-04
R&D DEPT.












9Pin Male Connector
Female Pin PCB Layout



Pin Assignments
Front View



Recommended Panel Cut-Out



Note: D
* QC Important Dimension To Check.
* Waterproof Rate: IP67, Unmated
* Housing: Thermoplastic, Black
* Pin: Copper Alloy, Gold Plated
* Nut: Thermoplastic, Black
* Gasket: Rubber, Black
B * Use with waterproof cap or dust cap
Panel Thickness Max: 3.0mm
B * Use without waterproof cap or dust cap
Panel Thickness Max: 4.0mm
* Gasket and Nut are packed separately in PE bags.

UNIT: mm

TOLERANCE
.X ±0.25
.XX ±0.1
.XXX ±0.05
ANGLES ±1°

TITLE: Middle
Panel Lock 9Pin M Conn M Pin

SCALE 1:1 | SIZE A4 | SHEET 1 OF 1
REV. D | WC-REV. A.3 | QC: Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
CD-09PMMP-LC7001	Ruru	2019-03-04
DWG NO: CD-09PMMP-LC7001	CHECKED BY: Rita	DATE: 2019-03-04
CUSTOMER: ALTW	APPROVED BY: Max	DATE: 2019-03-04

W10814-03-RW01A2

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

Unikeyic Electronics

Global Electronic Components Distributor

Click to view pricing, inventory, delivery, and lifecycle information:

AMPHENOL LTW:

DT-HCM-G3BMM-RLA60 M12A-04PFFS-SF8002 M12A04FR-12AFR-SD001 AD-03BMMA-LL7001 LAD-05BFFM-QR8D01 MSAP-12BMMA-SL7001 PWC-03BFFA-LL7002 RCP5SM-SPG06M-TL7B01 PWM-02BFMB-TL7001 Q8DU-05PMMS-QF8001 8-03PMMS-SH7002 FLBB-04FGMS-GCP-207 M12A-17BMMM-PL8D04 PWCU-04RMFS-LC7002 RCP5UM-UPG06M-TL7A01 DC-05BMFB-QL8APP FLKD-07EGFS-GCP-001 M12A04FL-12AFR-SDA05 CC-03BFMB-QL8APP DT-HCM-G3BFF-RLA60 M12A-03PMMS-SF8001 ASU-08PMMS-QC8A15 BSU-10PMMS-SC7001 DC-05BMMA-QL8MPP BD-03BFFA-QL8MP0 DD-18BMFA-LL7001 MSBP05MR-SBPMR-SB001 MSBS-05PFFR-SF7003 8-04PMMS-SH7002 ACC-03AFFM-LL7A01